Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	011-7S2488 F
	Issued	2015-03-17

Company holding the licence	ESC Energy Systems Company GmbH		Country	Austria
Brand (optional)			Website	www.estec-solar.at
Street, street number	Wirtschaftspark 14		E-mail	info@esc-solar.at
Postal Code / City, province	9130	Poggersdorf	Tel/Fax	43 (0)4224 821 88 - 0 / - 27

Collector Type (flat plate glazed/un-glazed; evacuate tubular)	Flat plate collector - glazed
Thermal / photo voltaic hybid collector? (PVT collector)	No
Integration in the roof possible ? (manufacturers declaration)	No

	Aperture area (Aa)	Gross length	Gross width	Gross height	Gross area (AG)	Power output per collector module G = 1000 W/m² Tm-Ta				
						0 K	10 K	30 K	50 K	70 K
Collector name	m²	mm	mm	mm	m²	W	W	W	W	W
FK 6260 N	2,29	2.077	1.238	100	2,57	1.747	1.667	1.482	1.264	1.013
FK 6260 L	2,30	1.238	2.078	100	2,57	1.748	1.666	1.474	1.245	980

Performance test method	Glazed liquid heating collector - steady state - indoor									
Performance parameters related to aperture area	η0	a1	a2							
Units	-	W/(m²K)	W/(m²K²)							
Test results - Flow rate and fluid see note 1	0,759	3,365	0,020							

Bi-directional incidence angle modifiers?	No	*Kϑ values are obligatory for 50°.*								
Incidence angle modifiers Kθ(θ)	Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
	Kθ(θ)					0,96				0,00
Incidence angle modifier not bi-directional - leave fields blank										

Stagnation temperature - Weather conditions see note 2	Tstg	198 °C
Effective thermal capacity	ceff = C/Ag	5,35 kJ/(m²K)
Max. intende operation temperature - see note 3	Tmax,op	- °C
Max. operation pressure - see note 3	pmax,op	1000 kPa

Pressure drop table - for a collector family, the values shall be for the module with highest ΔP per m² aperture area											
Flow rate	kg/(s m²)										
Pressure drop, ΔP	Pa										

Optional weather data	Location		Link	

Testing Laboratory	AIT Austrian Institute of Technology GmbH
Website	www.ait.ac.at
Test report id. number	2.04.00830.1.0-LT(6) & -QT(6); 2.04.00461.1.0-2a(3)
Date of test report	2015.03.17

During the test GDIF/GTOT was always between	0,1	and	0,2	

Comments of testing laboratory:

Note 1	Flow rate	0,020	kg/(s m²)	Fluid	Water
Note 2	Irradiance, G = 1000 W/m²; Ambient temperature , Ta=30 °C				
Note 3	Given by manufacturer				

AIT Austrian Institute of Technology GmbH
Donau-City-Straße 1 | 1220 Wien, Austria
T +43 (0) 50550-0 | F +43 (0) 50550-0
office@ait.ac.at | www.ait.ac.at

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	011-7S2488 F
	Issued	17.03.2015

Annual collector output kWh/module

Collector name	Location and collector temperature (Tm)											
	Athens			Davos			Stockholm			Würzburg		
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
FK 6260 N	2.829	2.025	1.283	2.154	1.464	866	1.593	1.029	590	1.732	1.116	629
FK 6260 L	2.845	2.036	1.290	2.166	1.472	871	1.602	1.034	593	1.741	1.123	633

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1.765	18,5	South, 25°
Davos	47	1.714	3,2	South, 30°
Stockholm	59	1.166	7,5	South, 45°
Würzburg	50	1.244	9,0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). A detailed description of the calculations is available at http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx.