

Annex to Solar Keymark Certificate					Licence Number		011-7S2161 F							
					Date issued		2021-12-20							
					Issued by		ISFH CalTeC							
Licence holder		AES Energietechnik GmbH			Country		Germany							
Brand (optional)					Web		www.aes-energiesysteme.de							
Street, Number		Hauptstr. 42			E-mail		info@aes-energiesysteme.de							
Postcode, City		D- 27412 Kirchtimke			Tel		+49 4289-9259070							
Collector Type					Flat plate collector									
Collector name					Power output per collector									
					$G_b = 850 \text{ W/m}^2, G_d = 150 \text{ W/m}^2 \text{ \& } u = 1.3 \text{ m/s}$									
					$\vartheta_m - \vartheta_a$									
					0 K	10 K	30 K	50 K	70 K	88 K				
					m ²	mm	mm	mm	mm	mm				
AES-REGENERATIO 2100					2.05	1952	1052	80	1487	1407	1235	1046	840	641
Power output per m² gross area					724	685	601	509	409	312				
Performance parameters test method		Steady state - indoor												
Performance parameters (related to A_G)		η_0, b	a1	a2	a3	a4	a5	a6	a7	a8	Kd			
Units		-	W/(m ² K)	W/(m ² K ²)	J/(m ³ K)	-	J/(m ² K)	s/m	W/(m ² K ⁴)	W/(m ² K ⁴)	-			
Test results		0.736	3.78	0.010			4 770				0.90			
Incidence angle modifier test method		Quasi dynamic - outdoor												
Incidence angle modifier		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°			
Transversal		$K_{\theta T, coll}$	1.00	0.99	0.98	0.96	0.94	0.88	0.78	0.45	0.00			
Longitudinal		$K_{\theta L, coll}$	1.00	0.99	0.98	0.96	0.94	0.88	0.78	0.45	0.00			
Heat transfer medium for testing					Water									
Flow rate for testing (per gross area, A_G)					dm/dt		0.096		kg/(sm²)					
Maximum temperature difference during thermal performance test					$(\vartheta_m - \vartheta_a)_{max}$		58		K					
Standard stagnation temperature (G = 1000 W/m²; $\vartheta_a = 30 \text{ }^\circ\text{C}$)					ϑ_{stg}		200		°C					
Maximum operating temperature					$\vartheta_{max, op}$		100		°C					
Maximum operating pressure					$p_{max, op}$		1000		kPa					
Testing laboratory		ISFH CalTeC			http://www.isfh.de									
Test report(s)		174-21/B			Dated		20.12.2021							
Comments of testing laboratory					Datasheet version: 6.1, 2019-07-11									
					Institut für Solarenergieforschung GmbH Am Ohrberg 1 D-31890 Emmenloot Tel.: 05151/999-100 Fax: 05151/999-500									
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de														

Annex to Solar Keymark Certificate		Licence Number		011-7S2161 F									
Supplementary Information		Issued		2021-12-20									
Annual collector output in kWh/collector at mean fluid temperature ϑ_m													
	Standard Locations	Athens			Davos			Stockholm			Würzburg		
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
AES-REGENERATIO 2100		2 348	1 624	1 028	1 752	1 178	718	1 295	821	482	1 410	885	511
Annual output per m ² gross area		1 143	791	501	853	574	350	631	400	235	687	431	249
Annual efficiency, η_a		65%	45%	28%	52%	35%	21%	54%	34%	20%	55%	35%	20%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (July 2019). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/													
Additional Information													
Collector heat transfer medium											Water-Glycole		
The collector is deemed to be suitable for roof integration											No		
The collector was tested successfully under the following conditions:													
Climate class (A+, A, B or C)											A		--
G (W/m ²) >		1000		ϑ_a (°C) >		20		H _x (MJ/m ²) >		600			
Maximum tested positive load											3030		Pa
Maximum tested negative load											2800		Pa
Hail resistance using steel ball (maximum drop height)											2		m
Additional collector attribute(s)													
<input type="checkbox"/> Using external power source(s) for normal operation <input type="checkbox"/> Active or passive measure(s) for self-protection <input type="checkbox"/> Co-generating thermal and electrical power <input type="checkbox"/> Façade collector(s)													
Energy Labelling Information						Additional Informative Technical Data							
		Reference Area, A _{sol} (m ²)				Hydraulic Designation Code				Aperture Area, A _a (m ²)			
AES-REGENERATIO 2100		2.05				1-VH-12S-A:11.3,12027				1.88			
Data required for CDR (EU) No 811/2013 - Reference Area A _{sol}						Data required for CDR (EU) No 812/2013 - Reference Area A _{sol}							
Collector efficiency (η_{col})		56%				Zero-loss efficiency (η_0)				0.72		--	
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.						First-order coefficient (a ₁)				3.78		W/(m ² K)	
						Second-order coefficient (a ₂)				0.010		W/(m ² K ²)	
						Incidence angle modifier IAM (50°)				0.92		--	
Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.													
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de													