Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S2457 F
	Date of issue	28.01.2015

Company	MHG Heiztechnik GmbH	**Country**		Deutschland
Brand (optional)		**Website**		www.mhg.de
Street, number	Brauerstraße 2	**E-mail**		kontakt@mhg.de
Postal Code	21244	**Tel.**	+49	41 812 355 350
City	Buchholz i.d.N.	**Fax**	+49	41 812 355 392

Collector Type (flat plate / evacuate tubular / un-glazed)	Flat plate collector
Integration in the roof possible ?	No

Collector name	Aperture area (Aa) [m²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (Ag) [m²]	Power output per collector unit G = 1000 W/m² Tm-Ta : 0 K [W]	10 K [W]	30 K [W]	50 K [W]	70 K [W]
SOLARMAT FL 2.3 MÄ	2.13	2 043	1 143	80	2.34	1 759	1 663	1 460	1 244	1 014

Collector efficiency parameters related to aperture area (Aa) Type of fluid and flow rate see note 1	η_{0a}	0.826	-
	a_{1a}	4.441	W/(m²K)
	a_{2a}	0.008	W/(m²K²)
Stagnation temperature - Weather conditions see note 2	t_{stg}	177	°C
Effective thermal capacity	$c_{eff} = C/A_a$	12.62	kJ/(m²K)
Max. operation pressure - see note 3	p_{max}	1000	kPa

Incidence angle modifiers $K_\theta(\theta)$	G_{DIF}/G_{TOT} min	G_{DIF}/G_{TOT} max	θ_T / θ_L	50°	*10°*	*20°*	*30°*	*40°*	*60°*	*70°*
			$K_\theta(\theta_T)$	0.92	1.00	0.99	0.98	0.96	0.86	0.73
	-	-	$K_\theta(\theta_L)$	0.92	1.00	0.99	0.98	0.96	0.86	0.73

G_{DIF}/G_{TOT}: min&max - while measuring — ***Optional values***

Testing Laboratory	TZS, ITW University of Stuttgart
Website	www.tzs.uni-stuttgart.de
Test report id. number	10COL871/1OEM08
Date of test report	28.01.2015
Perf. test method	EN 12975-2 6.1.4 (outdoor)

Comments of testing laboratory :

none

Note 1	**Fluid**	Water	**Flow rate**	0.020	kg/s per m²
Note 2	**Irradiance, Gs=1000 W/m²** **Ambient temperature , Ta=30 °C**				
Note 3	**Given by manufacturer**				

TZS Forschungs- und Testzentrum für Solaranlagen
Institut für Thermodynamik und Wärmetechnik
Universität Stuttgart
Pfaffenwaldring 6, 70550 Stuttgart (Vaihingen)

VERSION 3.6, 2012.01.13

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S2457 F
	Issued	28.01.2015

Annual collector output kWh

Collector name	Location and collector temperature (Tm)														
	Athens			Davos			Stockholm			Würzburg					
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C			
SOLARMAT FL 2.3 MÄ	2 749	1 894	1 214	2 194	1 471	911	1 511	962	577	1 644	1 034	611			

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). Detailed description with all equations used is available from the Solar Keymark web site (direct link: http://www.estif.org/solarkeymark/annexb1.php)

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin
Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de

Datasheet version:
VERSION 3.6, 2012.01.13
Calculation program version:
3.07, October 2011 (SP)