



Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate						Certificate No.		011-7S2451 F				
						Date of issue		15.12.2014				
Company		ORANIER Heiztechnik GmbH				Country		Deutschland				
Brand (optional)						Website		www.oranier.com				
Street, number		Weidenhäuser Str. 1-7				E-mail		info-heiztechnik@oranier.com				
Postal Code		35075				Tel.		+49 6462 923 455				
City		Gladenbach				Fax		+49 6 462 923 459				
Collector Type (flat plate / evacuate tubular / un-glazed)						Flat plate collector						
Integration in the roof possible ?						No						
Collector name	Aperture area (Aa) [m ²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (Ag) [m ²]	Power output per collector unit G = 1000 W/m ² Tm-Ta :						
						0 K	10 K	30 K	50 K	70 K		
FSK 230	2.13	2 043	1 143	80	2.34	1 759	1 663	1 460	1 244	1 014		
Collector efficiency parameters related to aperture area (Aa)						η_{0a}		0.826			-	
Type of fluid and flow rate see note 1						a_{1a}		4.441			W/(m ² K)	
						a_{2a}		0.008			W/(m ² K ²)	
Stagnation temperature - Weather conditions see note 2						t _{stg}		177			°C	
Effective thermal capacity						c _{eff} = C/Aa		12.62			kJ/(m ² K)	
Max. operation pressure - see note 3						p _{max}		1000			kPa	
Incidence angle modifiers K_θ(θ)	G_{DIF}/G_{TOT}		θ_T / θ_L	50°	10°	20°	30°	40°	60°	70°		
	min	max									K _θ (θ _T)	0.92
G _{DIF} /G _{TOT} : min&max - while measuring			K _θ (θ _L)	0.92	1.00	0.99	0.98	0.96	0.86	0.73		
						<i>Optional values</i>						
Testing Laboratory						TZS, ITW University of Stuttgart						
Website						www.tzs.uni-stuttgart.de						
Test report id. number						10COL871/10EM07						
Date of test report						15.12.2014						
Perf. test method						EN 12975-2 6.1.4 (outdoor)						
Comments of testing laboratory :												
-												
Note 1	Fluid	Water	Flow rate	0.020 kg/s per m ²								
Note 2	Irradiance, G _s =1000 W/m ²											
Note 2	Ambient temperature, T _a =30 °C											
Note 3	Given by manufacturer											



Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S2451 F
	Issued	15.12.2014

Annual collector output kWh														
Collector name	Location and collector temperature (T _m)													
	Athens			Davos			Stockholm			Würzburg				
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C		
FSK 230	2 749	1 894	1 214	2 194	1 471	911	1 511	962	577	1 644	1 034	611		

Collector mounting: Fixed or tracking Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations				
Location	Latitude °	Gtot kWh/m ²	Ta °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m ²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (T_m). Detailed description with all equations used is available from the Solar Keymark web site (direct link: <http://www.estif.org/solarkeymark/annexb1.php>)

DIN CERTCO • Alboinstraße 56 • 12103 Berlin Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de	Datasheet version: VERSION 3.6, 2012.01.13 Calculation program version: 3.07, October 2011 (SP)
---	--