



Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate		Certificate No.	011-7S2020 F
		Date of issue	19.09.2012
Company	CAMEL SOLAR LTD	Country	Republic of Macedonia
Brand (optional)		Website	www.camel-solar.com
Street, number	Veljko Vlahovic 18 (mezanin)	E-mail	v_ristov@hotmail.com
Postal Code	1000	Tel.	389 22 602 029
City	Skopje	Fax	389 23 229 600

Collector Type (flat plate / evacuate tubular / un-glazed) Flat plate collector

Integration in the roof possible ? No

Collector name	Aperture area (A _a) [m ²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (A _G) [m ²]	Power output per collector unit G = 1000 W/m ² T _m -T _a :				
						0 K	10 K	30 K	50 K	70 K
						[W]	[W]	[W]	[W]	[W]
CS Full Plate 2.0 -2	1.82	2 006	1 006	85	2.02	1 392	1 322	1 169	1 002	821
CS Full Plate 2.0 -4	1.83	2 005	1 005	85	2.02	1 400	1 329	1 176	1 008	825

Collector efficiency parameters related to aperture area (A _a) Type of fluid and flow rate see note 1	η _{0a}	0.765	-
	a _{1a}	3.785	W/(m ² K)
	a _{2a}	0.010	W/(m ² K ²)

Stagnation temperature - Weather conditions see note 2 t_{stg} 197 °C

Effective thermal capacity C_{eff} = C/A_a 14.37 kJ/(m²K)

Max. operation pressure - see note 3 p_{max} 1000 kPa

Incidence angle modifiers K _θ (θ)	G _{DIF} /G _{TOT}		θ _T / θ _L	50°	10°	20°	30°	40°	60°	70°
	min	max	K _θ (θ _T)	0.92	1.00	0.99	0.98	0.96	0.86	0.74
	-	-	K _θ (θ _L)	0.92	1.00	0.99	0.98	0.96	0.86	0.74
G _{DIF} /G _{TOT} : min&max - while measuring						<i>Optional values</i>				

Testing Laboratory	TZS, ITW University of Stuttgart
Website	www.tzs.uni-stuttgart.de
Test report id. number	12COL1116, 12COL1117, 12COL1117Q
Date of test report	19.09.2012
Perf. test method	EN 12975-2 6.1.4 (outdoor)

Comments of testing laboratory :
* dimensions according to manufacturer

Note 1	Fluid Water	Flow rate	0.020 kg/s per m ²	
Note 2	Irradiance, G_s=1000 W/m²			
Note 2	Ambient temperature, T_a=30 °C			
Note 3	Given by manufacturer			



**Annual collector output based on EN 12975 Test Results,
annex to Solar KEYMARK Certificate**

Certificate No.

011-7S2020 F

Issued

19.09.2012

Annual collector output kWh

Location and collector temperature (T_m)

Collector name	Location and collector temperature (T _m)											
	Athens			Davos			Stockholm			Würzburg		
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
CS Full Plate 2.0 -2	2 178	1 532	997	1 760	1 200	749	1 209	784	475	1 315	844	504
CS Full Plate 2.0 -4	2 190	1 540	1 002	1 770	1 207	753	1 216	788	478	1 322	849	507

Collector mounting: Fixed or tracking

Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (T_m). Detailed description with all equations used is available from the Solar Keymark web site (direct link: <http://www.estif.org/solarkeymark/annexb1.php>)

DIN CERTCO • Alboinstraße 56 • 12103 Berlin Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de	Datasheet version:
	VERSION 3.6, 2012.01.13
	Calculation program version:
	3.07, October 2011 (SP)