

Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate						Licence Number		011-7S2607 F				
						Issued		2016-01-26				
Company holding the		Kaltech Energy				Country		United Arab Emirates				
Brand (optional)						Website		www.kaltech.ae				
Street, street number		1322, Aspin commercial Tower ,Sheik Zayed				E-mail		aliyu@kaltechenergy.com				
Postal Code / City, province		Dubai				Tel/Fax		+971 04 2567 708 / 04 2567 709				
Collector Type (flat plate glazed/un-glazed; evacuate tubular)						Flat plate collector - glazed						
Thermal / photo voltaic hybrid collector? (PVT collector)						No						
Integration in the roof possible ? (manufacturers declaration)						No						
Collector name	Aperture area (Aa)	Gross length	Gross width	Gross height	Gross area (AG)	Power output per collector module						
						G = 1000 W/m²						
						Tm-Ta						
						0 K	10 K	30 K	50 K	70 K		
						W	W	W	W	W		
KE2.OR	1.91	2 030	1 027	92	2.08	1 423	1 352	1 190	1 002	788		
KE2.5R	2.29	2 032	1 230	93	2.50	1 706	1 621	1 427	1 202	945		
Performance test method						Glazed liquid heating collector - steady state - outdoor						
Performance parameters related to aperture area		η_0	a1	a2								
Units		-	W/(m ² K)	W/(m ² K ²)								
Test results - Flow rate and fluid see note 1		0.745	3.556	0.017								
Bi-directional incidence angle modifiers?		No										
		<i>Kθ values are obligatory for 50°.</i>										
Incidence angle modifiers Kθ(θ)		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°	
		K θ (θ)	1.00	0.98	0.96	0.92	0.85	0.74	0.49	0.00	0.00	
Incidence angle modifier not bi-directional - leave fields blank												
Stagnation temperature - Weather conditions see note 2						Tstg	193	°C				
Effective thermal capacity						ceff = C/AAp	10.57	kJ/(m²K)				
Max. intended operation temperature - see note 3						Tmax,op	-	°C				
Max. operation pressure - see note 3						pmax,op	1000	kPa				
Pressure drop table - for a collector family, the values shall be for the module with highest ΔP per m² aperture area												
Flow rate	kg/(s m ²)	-	-	-	-	-	-	-	-	-	-	
Pressure drop, ΔP	Pa	-	-	-	-	-	-	-	-	-	-	
Optional weather data		Location						Link				
Testing Laboratory		TZS, ITW University Stuttgart										
Website		http://www.itw.uni-stuttgart.de										
Test report id. number		08COL678/10EM14				Date of test report		2016.01.26				
During the test GDIF/GTOT was always between		0	and	1								
Comments of testing laboratory:												
none												
Note 1	Flow rate	0.020	kg/(s m ²)	Fluid	Water							
Note 2	Irradiance, G = 1000 W/m²; Ambient temperature, Ta=30 °C											
Note 3	Given by manufacturer											
Datasheet version: 4.06, 2014-01-15												
DIN CERTCO • Albainstraße 56 • 12103 Berlin Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de												

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	011-7S2607 F
	Issued	26.01.2016

Annual collector output kWh/module														
Collector name	Location and collector temperature (T _m)													
	Athens			Davos			Stockholm			Würzburg				
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C		
KE2.0R	2 093	1 437	882	1 576	1 047	611	1 156	731	417	1 253	780	436		
KE2.5R	2 510	1 723	1 057	1 889	1 256	732	1 386	876	500	1 502	935	522		

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)
---------------------------------------	---

Overview of locations				
Location	Latitude °	G _{tot} kWh/m ²	T _a °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

G _{tot}	Annual total irradiation on collector plane	kWh/m ²
T _a	Mean annual ambient air temperature	°C
T _m	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (T_m). A detailed description of the calculations is available at <http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx>.

DIN CERTCO • Alboinstraße 56 • 12103 Berlin Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de	Datasheet version: 4.06, 2014-01-15
	ScenoCalc version: Ver. 4.06 (Jan, 2014)