Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate		Licence Number	011-7S012 F
		Issued	2014-10-13

Company holding the	Solahart Australia Pty Ltd		Country	Australia	
Brand (optional)			Website	www.solahart.com.au	
Street, street number	112 Pilbara Street		E-mail	solahart@solahart.com.au	
Postal Code / City, province	6106	Welshpool WA	Tel/Fax	61	893514600 / 8 9351 4698

Collector Type (flat plate glazed/un-glazed; evacuate tubular)	Flat plate collector - glazed
Thermal / photo voltaic hybid collector? (PVT collector)	No
Integration in the roof possible ? (manufacturers declaration)	No

Collector name	Aperture area (Aa)	Gross length	Gross width	Gross height	Gross area (AG)	Power output per collector module Gb = 850 W/m²; Gd = 150 W/m² Tm-Ta 0 K	10 K	30 K	50 K	70 K
	m²	mm	mm	mm	**m²**	W	W	W	W	W
Bt Collector	1.87	1 942	1 032	83	**2.00**	1 507	1 427	1 253	1 061	851

Performance test method	Liquid heating collector - quasi-dynamic - outdoor							
Performance parameters related to aperture area	η0b	c1	c2	c3	c4	c6	Kθd	
Units	-	W/(m²K)	W/(m²K²)	J/(m³K)	-	s/m	-	
Test results - Flow rate and fluid see note 1	0.810	4.168	0.012	0.000	0.000	0.000	0.966	

Bi-directional incidence angle modifiers?	No	*Kϑ values are obligatory for 50°.*								
Incidence angle modifiers Kθ(θ)	Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
	Kθ(θ)	1.00	0.99	0.98	0.96	0.93	0.87	0.75	0.39	0.00
Incidence angle modifier not bi-directional - leave fields blank										

Stagnation temperature - Weather conditions see note 2	Tstg	189	°C
Effective thermal capacity	ceff = C/Ag	10.614	kJ/(m²K)
Max. intende operation temperature - see note 3	Tmax,op	100	°C
Max. operation pressure - see note 3	pmax,op	1400	kPa

Pressure drop table - for a collector family, the values shall be for the module with highest ΔP per m² aperture area											
Flow rate	kg/(s m²)	-	-	-	-	-	-	-	-	-	-
Pressure drop, ΔP	Pa		-	-	-	-	-	-	-	-	-

Optional weather data	Location		Link	
Testing Laboratory	TZS, ITW University Stuttgart			
Website	http://www.itw.uni-stuttgart.de			
Test report id. number	14COL1212, 14COL1212Q	Date of test report	2014.10.13	
During the test GDIF/GTOT was always between	0	and	1	

Comments of testing laboratory:

Note 1	Flow rate	0.020	kg/(s m²)	Fluid	Water
Note 2	Irradiance, G = 1000 W/m²; Ambient temperature , Ta=30 °C				
Note 3	Given by manufacturer				

Datasheet version: 4.06, 2014-01-15

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin
Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	011-7S012 F
	Issued	13.10.2014

Annual collector output kWh/module

Collector name	Location and collector temperature (Tm)											
	Athens			Davos			Stockholm			Würzburg		
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
Bt Collector	2 426	1 689	1 074	1 812	1 220	742	1 340	852	500	1 465	925	533

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). A detailed description of the calculations is available at http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx.

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin
Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de

Datasheet version: 4.06, 2014-01-15

ScenoCalc version: Ver. 4.06 (Jan, 2014)