

Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate						Licence Number		<b>011-7S2453 F</b>			
						Issued		2014-12-18			
Company holding the		Energy Panel S.L.				Country		Spain			
Brand (optional)						Website		www.energypanel.es			
Street, street number		Ctra. Lucena-Loja, km. 1,7				E-mail		energypanel@energypanel.es			
Postal Code / City, province		14900		Lucena (Córdoba)		Tel/Fax		34 957 509 537 / 957 502 441			
Collector Type (flat plate glazed/un-glazed; evacuate tubular)						Flat plate collector - un-glazed					
Thermal / photo voltaic hybrid collector? (PVT collector)						No					
Integration in the roof possible ? (manufacturers declaration)						Yes					
							Power output per collector module				
							Gb = 850 W/m <sup>2</sup> ; Gd = 150 W/m <sup>2</sup> ; Tm-Ta = 2 K				
							Wind velocity				
							0 m/s		1.5 m/s		3 m/s
Collector name		Aperture area (Aa)	Gross length	Gross width	Gross height	Gross area (AG)	W	W	W		
Solar Panel STD01		1.36	1700	800	22	1.36	1102	1074	1046		
Performance test method											
		Liquid heating collector - quasi-dynamic - outdoor									
Performance parameters related to aperture area		η <sub>0b</sub>	c <sub>1</sub>	c <sub>2</sub>	c <sub>3</sub>	c <sub>4</sub>	c <sub>6</sub>	Kθd			
Units		-	W/(m <sup>2</sup> K)	W/(m <sup>2</sup> K <sup>2</sup> )	J/(m <sup>3</sup> K)	-	s/m	-			
Test results - Flow rate and fluid see note 1		0.913	9.767	0.000	6.910	0.808	0.000	0.985			
Bi-directional incidence angle modifiers?		No	<i>Kθ values are obligatory for 50°.</i>								
Incidence angle modifiers Kθ(θ)		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
		Kθ(θ)	1.00	1.00	1.00	1.00	0.99	0.98	0.95	0.48	0.00
Incidence angle modifier not bi-directional - leave fields blank											
Stagnation temperature - Weather conditions see note 2						T <sub>stg</sub>		69		°C	
Effective thermal capacity						c <sub>eff</sub> = C/Ag		8.8		kJ/(m <sup>2</sup> K)	
Max. intended operation temperature - see note 3						T <sub>max,op</sub>		-		°C	
Max. operation pressure - see note 3						p <sub>max,op</sub>		1000		kPa	
Pressure drop table - for a collector family, the values shall be for the module with highest ΔP per m <sup>2</sup> aperture area											
Flow rate		kg/(s m <sup>2</sup> )	-	-	-	-	-	-	-	-	-
Pressure drop, ΔP		Pa	-	-	-	-	-	-	-	-	-
Optional weather data		Location				Link					
Testing Laboratory		TZS, ITW University of Stuttgart									
Website		www.tzs.uni-stuttgart.de									
Test report id. number		14COL1232				Date of test report		2014.12.18			
During the test GDIF/GTOT was always between		0	and	1							
Comments of testing laboratory:											
This solar collector can also be used as an evaporator in a heat pump circuit using a refrigerant fluid as heat transfer fluid.											
Note 1		Flow rate	0.020	kg/(s m <sup>2</sup> )	Fluid	Water					
Note 2		Irradiance, G = 1000 W/m <sup>2</sup> ; Ambient temperature, T <sub>a</sub> = 30 °C									
Note 3		Given by manufacturer									
						Datasheet version: 4.06, 2014-01-15					
<b>DIN CERTCO • Alboinstraße 56 • 12103 Berlin</b> <b>Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de •</b> <b>www.dincertco.de</b>											

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	011-7S2453 F
	Issued	18.12.2014

Annual collector output kWh/module														
Collector name	Location and collector temperature (T <sub>m</sub> )													
	Athens			Davos			Stockholm			Würzburg				
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C		
Solar Panel STD01	1 547	167	8	626	55	0	554	61	2	651	91	7		

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)
---------------------------------------	-------------------------------------------------------

Overview of locations				
Location	Latitude °	G <sub>tot</sub> kWh/m <sup>2</sup>	T <sub>a</sub> °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

G <sub>tot</sub>	Annual total irradiation on collector plane	kWh/m <sup>2</sup>
T <sub>a</sub>	Mean annual ambient air temperature	°C
T <sub>m</sub>	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (T<sub>m</sub>). A detailed description of the calculations is available at <http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx>.

<b>DIN CERTCO • Alboinstraße 56 • 12103 Berlin</b> <b>Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de •</b> <b>www.dincertco.de</b>	Datasheet version: 4.06, 2014-01-15
	ScenoCalc version: Ver. 4.06 (Jan, 2014)