


<b>Annex to Solar Keymark Certificate</b>					<b>Licence Number</b>		<b>011-7S2476 F</b>								
					<b>Date issued</b>		<b>2023-06-26</b>								
					<b>Issued by</b>		<b>DIN CERTCO</b>								
<b>Licence holder</b>		<b>DIMAS SA (RADIANT)</b>			<b>Country</b>		Greece								
<b>Brand (optional)</b>		RADIANT ECO SOLUTIONS			<b>Web</b>										
<b>Street, Number</b>		2ND KM ARGOS-NAFPLIO			<b>E-mail</b>		info@dimas-solar.gr								
<b>Postcode, City</b>		21200 ARGOS			<b>Tel</b>		+30 27510 20920								
<b>Collector Type</b>					Flat plate collector										
<b>Collector name</b>					<b>Power output per collector</b> G <sub>b</sub> = 850 W/m <sup>2</sup> , G <sub>d</sub> = 150 W/m <sup>2</sup> & u = 1.3 m/s $\vartheta_m - \vartheta_a$										
					0 K	10 K	30 K	50 K	70 K	112 K					
					m <sup>2</sup>	mm	mm	mm	mm	W	W	W	W	W	W
<b>RSV 15</b>					1.51	1.503	1.007	85	1.093	1.037	921	797	666	367	
<b>RSV 17</b>					1.68	1.420	1.183	85	1.216	1.154	1.024	886	741	408	
<b>RSV 19</b>					1.96	1.503	1.305	85	1.419	1.346	1.195	1.034	864	476	
<b>RSV 20</b>					2.02	2.006	1.007	85	1.462	1.388	1.232	1.066	890	490	
<b>RSV 23</b>					2.24	1.893	1.183	85	1.621	1.539	1.366	1.182	987	544	
<b>RSV 25</b>					2.52	2.006	1.257	85	1.824	1.731	1.536	1.330	1.111	612	
<b>RSV 27</b>					2.67	2.261	1.183	85	1.933	1.834	1.628	1.409	1.177	648	
<b>RSV 29</b>					2.92	2.006	1.457	85	2.114	2.006	1.780	1.541	1.287	709	
<b>Power output per m<sup>2</sup> gross area</b>					724	687	610	528	441	243					
<b>Performance parameters test method</b>		Quasi dynamic													
<b>Performance parameters (related to A<sub>G</sub>)</b>		$\eta_0, b$	a1	a2	a3	a4	a5	a6	a7	a8	Kd				
<b>Units</b>		-	W/(m <sup>2</sup> K)	W/(m <sup>2</sup> K <sup>2</sup> )	J/(m <sup>3</sup> K)	-	J/(m <sup>2</sup> K)	s/m	W/(m <sup>2</sup> K <sup>4</sup> )	W/(m <sup>2</sup> K <sup>4</sup> )	-				
<b>Test results</b>		0.725	3.62	0.006	0.000	0.00	13.660	0.000	0.00	0.00	0.99				
<b>Incidence angle modifier test method</b>		Quasi dynamic - outdoor													
<b>Incidence angle modifier</b>		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°				
<b>Transversal</b>		K <sub>θT, coll</sub>	1.00	1.00	1.00	0.99	0.96	0.87	0.63	0.32	0.00				
<b>Longitudinal</b>		K <sub>θL, coll</sub>	1.00	1.00	1.00	0.99	0.96	0.87	0.63	0.32	0.00				
<b>Heat transfer medium for testing</b>		Water													
<b>Flow rate for testing (per gross area, A<sub>G</sub>)</b>		dm/dt	0.020	kg/(sm <sup>2</sup> )											
<b>Maximum temperature difference during thermal performance test</b>		( $\vartheta_m - \vartheta_a$ ) <sub>max</sub>	82	K											
<b>Standard stagnation temperature (G = 1000 W/m<sup>2</sup>; <math>\vartheta_a</math> = 30 °C)</b>		$\vartheta_{stg}$	230	°C											
<b>Maximum operating temperature</b>		$\vartheta_{max, op}$	-	°C											
<b>Maximum operating pressure</b>		p <sub>max, op</sub>	1000	kPa											
<b>Testing laboratory</b>		Institut für Gebäudeenergetik, Thermotechnik und Energiespeicherung (IGTE)					http://www.igte.uni-stuttgart.de								
<b>Test report(s)</b>		21COL1631OEM12 21COL1631QOEM12 21COL1632OEM12					<b>Dated</b>		12.06.2023 12.06.2023 12.06.2023						
<b>Comments of testing laboratory</b>		Ver. 6.2 (13.01.2022)													
<b>Documented performance parameters are taken from 21COL1632OEM12 (RSV 15)</b>		 Forschungs- und Testzentrum für Solaranlagen Institut für Thermodynamik und Wärmetechnik Universität Stuttgart Plaffenwaldring 6, 70550 Stuttgart (Vaihingen)													
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de															

Annex to Solar Keymark Certificate		Licence Number		011-7S2476 F							
Supplementary Information		Issued		2023-06-26							
<b>Gross Thermal Yield in kWh/collector at mean fluid temperature <math>\vartheta_m</math></b>											
Standard Locations		Athens		Davos		Stockholm		Würzburg			
Collector name	$\vartheta_m$	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	
RSV 15		1.091	719	449	1.091	719	449	1.091	719	449	
RSV 17		1.214	800	500	1.214	800	500	1.214	800	500	
RSV 19		1.416	934	583	1.416	934	583	1.416	934	583	
RSV 20		1.460	962	601	1.460	962	601	1.460	962	601	
RSV 23		1.618	1.067	666	1.618	1.067	666	1.618	1.067	666	
RSV 25		1.821	1.200	750	1.821	1.200	750	1.821	1.200	750	
RSV 27		1.929	1.272	794	1.929	1.272	794	1.929	1.272	794	
RSV 29		2.110	1.391	869	2.110	1.391	869	2.110	1.391	869	
Gross Thermal Yield per m <sup>2</sup> gross area		723	476	298	723	476	298	723	476	298	
Annual efficiency, $\eta_a$		41%	27%	17%	44%	29%	18%	62%	41%	26%	
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)									
Annual irradiation on collector plane		1765 kWh/m <sup>2</sup>			1630 kWh/m <sup>2</sup>			1166 kWh/m <sup>2</sup>		1244 kWh/m <sup>2</sup>	
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C		9.0°C	
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°		South, 35°	
The collector is operated at constant temperature $\vartheta_m$ (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.2 (13.01.2022). A detailed description of the calculations is available at <a href="http://www.estif.org/solarkeymarknew/">http://www.estif.org/solarkeymarknew/</a>											
<b>Additional Information</b>											
Collector heat transfer medium				Water-Glycole							
The collector is deemed to be suitable for roof integration				No							
The collector was tested successfully under the following conditions:											
Climate class (A+, A, B or C)				A							
G (W/m <sup>2</sup> ) >		1000		$\vartheta_a$ (°C) >		20		H <sub>x</sub> (MJ/m <sup>2</sup> ) >		600	
Maximum tested positive load				2750		Pa					
Maximum tested negative load				2400		Pa					
Hail resistance using steel ball (maximum drop height)				2		m					
<b>Additional collector attribute(s)</b>											
Using external power source(s) for normal operation		No		Active or passive measure(s) for self-protection		No					
Co-generating thermal and electrical power		No		Façade collector(s)		No					
<b>Energy Labelling Information</b>			<b>Additional Informative Technical Data</b>								
	Reference Area, A <sub>sol</sub> (m <sup>2</sup> )	Hydraulic Designation Code		Aperture Area, A <sub>a</sub> (m <sup>2</sup> )							
RSV 15	1.51	8-V-1234S-7.2,1383-20.6,1060-D		1.36							
RSV 17	1.68	10-V-1234S-7.2,1303-20.6,1240-D		1.52							
RSV 19	1.96	11-V-1234S-7.2,1383-20.6,1370-D		1.79							
RSV 20	2.02	8-V-1234S-7.2,1888-20.6,1060-D		1.83							
RSV 23	2.24	10-V-1234S-7.2,1773-20.6,1240-D		2.05							
RSV 25	2.52	11-V-1234S-7.2,1888-20.6,1310-D		2.32							
RSV 27	2.67	10-V-1234S-7.2,2143-20.6,1240-D		2.46							
RSV 29	2.92	12-V-1234S-7.2,1888-20.6,1510-D		2.71							
<b>Data required for CDR (EU) No 811/2013 - Reference Area</b>			<b>Data required for CDR (EU) No 812/2013 - Reference Area A<sub>sol</sub></b>								
Collector efficiency ( $\eta_{col}$ )			57%		Zero-loss efficiency ( $\eta_0$ )		0.72		--		
Remark: Collector efficiency ( $\eta_{col}$ ) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m <sup>2</sup> , expressed in % and rounded to the nearest integer. Deviating from the regulation $\eta_{col}$ is based on reference area (A <sub>sol</sub> ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.			First-order coefficient (a <sub>1</sub> )		3.62		W/(m <sup>2</sup> K)				
			Second-order coefficient (a <sub>2</sub> )		0.006		W/(m <sup>2</sup> K <sup>2</sup> )				
			Incidence angle modifier IAM (50°)		0.98		--				
Remark: The data given in this section are related to collector reference area (A <sub>sol</sub> ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.											
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany											
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de											