



Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate		Certificate No.	011-7S2136 F
		Date of issue	13.05.2013
Company	PROTHERM PRODUCTION s.r.o.	Country	Slowakei
Brand (optional)		Website	www.protherm.sk
Street, number	Jurkovicova 45	E-mail	Marc.imann@vaillant.de
Postal Code	90901	Tel.	+49 2 191 182 043
City	Skalica	Fax	+49 21 911 872 043

Collector Type (flat plate / evacuate tubular / un-glazed)	Flat plate collector
---	----------------------

Integration in the roof possible ?	Yes
---	-----

Collector name	Aperture area (Aa) [m ²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (Ag) [m ²]	Power output per collector unit G = 1000 W/m ² Tm-Ta :				
						0 K	10 K	30 K	50 K	70 K
						[W]	[W]	[W]	[W]	[W]
SCV 1.9*	1.92	1 988	1 041	90	2.07	1 507	1 433	1 272	1 092	894

Collector efficiency parameters related to aperture area (Aa) Type of fluid and flow rate see note 1	η_{0a}	0.785	-
	a_{1a}	3.722	W/(m ² K)
	a_{2a}	0.012	W/(m ² K ²)

Stagnation temperature - Weather conditions see note 2	t_{stg}	203	°C
---	-----------	-----	----

Effective thermal capacity	$c_{eff} = C/Aa$	9.54	kJ/(m ² K)
-----------------------------------	------------------	------	-----------------------

Max. operation pressure - see note 3	p_{max}	1000	kPa
---	-----------	------	-----

Incidence angle modifiers $K_{\theta}(\theta)$	G_{DIF}/G_{TOT}		θ_T / θ_L	50°	10°	20°	30°	40°	60°	70°
	min	max	$K_{\theta}(\theta_T)$	0.94	1.00	0.99	0.98	0.97	0.90	0.80
	-	-	$K_{\theta}(\theta_L)$	0.94	1.00	0.99	0.98	0.97	0.90	0.80
G_{DIF}/G_{TOT} : min&max - while measuring						Optional values				

Testing Laboratory	TZS, ITW University of Stuttgart
Website	www.tzs.uni-stuttgart.de
Test report id. number	12COL1079OEM14, 12COL1079QOEM14
Date of test report	13.05.2013
Perf. test method	EN 12975-2 6.1.4 (outdoor)

Comments of testing laboratory :
* dimensions according to manufacturer

Note 1	Fluid	Water	Flow rate	0.020 kg/s per m ²
Note 2	Irradiance, $G_s=1000$ W/m²			
	Ambient temperature, $T_a=30$ °C			
Note 3	Given by manufacturer			





Annual collector output based on EN 12975 Test Results,
annex to Solar KEYMARK Certificate

Certificate No.

011-7S2136 F

Issued

13.05.2013

Annual collector output kWh

Location and collector temperature (T_m)

Collector name	Location and collector temperature (T _m)														
	Athens			Davos			Stockholm			Würzburg					
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C			
SCV 1.9*	2 443	1 749	1 154	1 989	1 372	859	1 368	897	546	1 489	973	583			

Collector mounting: Fixed or tracking

Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	G _{tot} kWh/m ²	T _a °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

G _{tot}	Annual total irradiation on collector plane	kWh/m ²
T _a	Mean annual ambient air temperature	°C
T _m	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (T_m). Detailed description with all equations used is available from the Solar Keymark web site (direct link: <http://www.estif.org/solarkeymark/annexb1.php>)

DIN CERTCO • Alboinstraße 56 • 12103 Berlin

Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de

Datasheet version:

VERSION 3.6, 2012.01.13

Calculation program version:

3.07, October 2011 (SP)