Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	011-7S2554 F
	Issued	2015-06-29

Company holding the	ratiotherm GmbH & Co KG		Country	Germany
Brand (optional)			Website	www.ratiotherm.de
Street, street number	Weilheimer Str. 34		E-mail	info@ratiotherm.de
Postal Code / City, province	91795	Dollnstein	Tel/Fax	08422 9977 0

Collector Type (flat plate glazed/un-glazed; evacuate tubular)	Flat plate collector - glazed
Thermal / photo voltaic hybid collector? (PVT collector)	No
Integration in the roof possible ? (manufacturers declaration)	No

Collector name	Aperture area (Aa)	Gross length	Gross width	Gross height	Gross area (AG)	Power output per collector module G = 1000 W/m², Tm-Ta 0 K	10 K	30 K	50 K	70 K
	m²	mm	mm	mm	**m²**	W	W	W	W	W
RA 215	1,90	2.010	1.068	90	**2,15**	1.460	1.386	1.233	1.072	903

Performance test method	Glazed liquid heating collector - steady state - outdoor									
Performance parameters related to aperture area	η0	a1	a2							
Units	-	W/(m²K)	W/(m²K²)							
Test results - Flow rate and fluid see note 1	0,767	3,826	0,005							

Bi-directional incidence angle modifiers?	No	*Kϑ values are obligatory for 50°.*								
Incidence angle modifiers Kθ(θ)	Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
	Kθ(θ)	1,00	0,99	0,99	0,97	0,94	0,86	0,73	0,47	0,00
Incidence angle modifier not bi-directional - leave fields blank										

Stagnation temperature - Weather conditions see note 2	Tstg	198	°C
Effective thermal capacity	ceff = C/Ag	4,9,	kJ/(m²K)
Max. intended operation temperature - see note 3	Tmax,op	160	°C
Max. operation pressure - see note 3	pmax,op	1000	kPa

Pressure drop table - for a collector family, the values shall be for the module with highest ΔP per m² aperture area

Flow rate	kg/(s m²)										
Pressure drop, ΔP	Pa										

Testing Laboratory	TestLab Solar Thermal Systems, Fraunhofer ISE			
Website	www.collectortest.com			
Test report id. number	ktb-2006-18-h	Date of test report	2015.06.29	
During the test GDIF/GTOT was always between	0,1	and	0,2	

Comments of testing laboratory:

The pressure drop was not determined.

Note 1	Flow rate	0,020	kg/(s m²)	Fluid	Water
Note 2	Irradiance, G = 1000 W/m²; Ambient temperature , Ta=30 °C				
Note 3	Given by manufacturer				

TestLab
Solar Thermal
Systems
Heidenhofstraße 2
D-79110 Freiburg
Tel: +49 (0)761 4588 5354

Version: 4.06, 2014-01-15

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	011-7S2554 F
	Issued	29.06.2015

Annual collector output kWh/module

Collector name	Location and collector temperature (Tm)											
	Athens			Davos			Stockholm			Würzburg		
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
RA 215	2.310	1.648	1.117	1.752	1.235	826	1.286	852	544	1.398	919	578

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1.765	18,5	South, 25°
Davos	47	1.714	3,2	South, 30°
Stockholm	59	1.166	7,5	South, 45°
Würzburg	50	1.244	9,0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). A detailed description of the calculations is available at http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx.

DIN CERTCO • Alboinstraße 56 • 12103 Berlin
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de •
www.dincertco.de

Datasheet version: 4.06, 2014-01-15

ScenoCalc version: Ver. 4.06 (Jan, 2014)