



Annex to Solar Keymark Certificate Supplementary Information	Licence Number	011-7S2573 F
	Issued	2018-04-11

Annual collector output in kWh/collector at mean fluid temperature  $\vartheta_m$ , based on ISO 9806:2013 test results

Collector name	Standard Locations $\vartheta_m$	Athens			Davos			Stockholm			Würzburg		
		25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
UNIKO P21		2.635	1.940	1.315	2.035	1.448	941	1.496	1.010	632	1.624	1.094	673
KSF P26		3.352	2.467	1.672	2.589	1.842	1.197	1.903	1.285	804	2.065	1.392	855
Annual output per m <sup>2</sup> gross area		1.279	942	638	988	703	457	726	490	307	788	531	327
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m <sup>2</sup>			1714 kWh/m <sup>2</sup>			1166 kWh/m <sup>2</sup>			1244 kWh/m <sup>2</sup>		
Mean annual ambient air temperature		18,5°C			3,2°C			7,5°C			9,0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature  $\vartheta_m$  (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 5.01 (March 2016). A detailed description of the calculations is available at [www.solarkeymark.org/scenocalc](http://www.solarkeymark.org/scenocalc)

**Additional Information**

Collector heat transfer medium	Water-Glycole	
Hybrid Thermal and Photo Voltaic collector	No	
The collector is deemed to be suitable for roof integration	Yes	
The collector was tested successfully according to EN ISO 9806:2013 under the following conditions:		
Climate class (A, B or C)	A	--
Maximum tested positive load	2400	Pa
Maximum tested negative load	2400	Pa
Hail resistance using ice balls (diameter)	25	mm

**Energy Labeling Information**

	Reference Area, $A_{sol}$ (m <sup>2</sup> )	Data required for CDR (EU) No 811/2013 - Reference Area $A_{sol}$			
UNIKO P21	2,06	Collector efficiency ( $\eta_{col}$ )	63 %		
KSF P26	2,62	<i>Remark: Collector efficiency (<math>\eta_{col}</math>) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m<sup>2</sup>, expressed in % and rounded to the nearest integer. Deviating from the regulation <math>\eta_{col}</math> is based on reference area (<math>A_{sol}</math>) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2013.</i>			
	Data required for CDR (EU) No 812/2013 - Reference Area $A_{sol}$				
	Zero-loss efficiency ( $\eta_0$ )			0,791	--
	First-order coefficient ( $a_1$ )			3,34	W/(m <sup>2</sup> K)
	Second-order coefficient ( $a_2$ )			0,014	W/(m <sup>2</sup> K <sup>2</sup> )
	Incidence angle modifier IAM (50°)	0,95	--		
<i>Remark: The data given in this section are related to collector reference area (<math>A_{sol}</math>) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.</i>					