


Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate						Licence Number		011-7S2608 F			
						Issued		2015-12-01			
Company holding the		Hewalex Sp. z. o. o. Sp. K.				Country		POLAND			
Brand (optional)		--				Website		www.hewalex.pl			
Street, street number		Slowackiego 33				E-mail		hewalex@hewalex.pl			
Postal Code / City, province		43-502		Czechowice-Dziedzice		Tel/Fax		32 214 17 10 / 50 04			
Collector Type (flat plate glazed/un-glazed; evacuate tubular)						Flat plate collector - glazed					
Thermal / photo voltaic hybrid collector? (PVT collector)						No					
Integration in the roof possible? (manufacturers declaration)						Yes					
Collector name	Aperture area (Aa) m ²	Gross length mm	Gross width mm	Gross height mm	Gross area (AG) m ²	Power output per collector module					
						G = 1000 W/m ²					
						Tm-Ta					
						0 K	10 K	30 K	50 K	70 K	
KS 2100 NLP AM	1,83	2.018	1.037	86	2,09	W	W	W	W	W	
						1.389	1.318	1.164	992	803	
Performance test method						Glazed liquid heating collector - steady state - indoor					
Performance parameters related to aperture area		η_0	a1	a2							
Units		-	W/(m ² K)	W/(m ² K ²)							
Test results - Flow rate and fluid see note 1		0,759	3,735	0,012							
Bi-directional incidence angle modifiers?		No <i>Kθ values are obligatory for 50°.</i>									
Incidence angle modifiers K θ (θ)		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
		K θ (θ)					0,94				0,00
Incidence angle modifier not bi-directional - leave fields blank											
Stagnation temperature - Weather conditions see note 2						Tstg	210,1 °C				
Effective thermal capacity						ceff = C/Ag	5,557 kJ/(m ² K)				
Max. intended operation temperature - see note 3						Tmax,op	250 °C				
Max. operation pressure - see note 3						pmax,op	1000 kPa				
Pressure drop table - for a collector family, the values shall be for the module with highest ΔP per m ² aperture area											
Flow rate	kg/(s m ²)	0,000	0,008	0,020	0,030	0,042	0,053				
Pressure drop, ΔP	Pa	0	2257	8189	15845	27779	42946				
Optional weather data		Location				Link					
Testing Laboratory		Fundación CENER-CIEMAT, LEST									
Website		www.cener.com									
Test report id. number		30.2778.0-1-1 / 30.2778.0-2-1				Date of test report		2015/11/16			
During the test GDIF/GTOT was always between		0,11	and	0,12							
Comments of testing laboratory:											
--											
Note 1	Flow rate	0,027 kg/(s m ²)	Fluid	Water							
Note 2	Irradiance, G = 1000 W/m ² ; Ambient temperature, Ta = 30 °C										
Note 3	Given by manufacturer										
						 ADItech Datasheet version: 4.06, 2014-01-15					
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de											

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	011-7S2608 F
	Issued	01/12/2015

Annual collector output kWh/module													
Collector name	Location and collector temperature (Tm)												
	Athens			Davos			Stockholm			Würzburg			
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	
KS 2100 NLP AM	2.214	1.560	1.006	1.669	1.140	706	1.232	795	474	1.339	858	503	

Collector mounting: Fixed or tracking Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations				
Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1.765	18,5	South, 25°
Davos	47	1.714	3,2	South, 30°
Stockholm	59	1.166	7,5	South, 45°
Würzburg	50	1.244	9,0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). A detailed description of the calculations is available at <http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx>.