TÜVRheinland®
DIN CERTCO

Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence number	011-7S671 F
	Date of issue	14.04.2015

Company holding the licence	Westfalen AG	**Country**		Germany
Brand (optional)	-	**Website**		www.westfalen-ag.de
Street, number	Industrieweg 43	**E-mail**		info@westfalen-ag.de
Postal Code	48155	**Tel.**	+49	(0)251 - 695 290
City	Münster	**Fax**	+49	(0)251 - 695 73 290

Collector Type (flat plate / evacuate tubular / un-glazed)	Flat plate collector
Integration in the roof possible ?	No

Collector name	Aperture area (Aa) [m²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (AG) [m²]	Power output per collector unit G = 1000 W/m² Tm-Ta : 0 K [W]	10 K [W]	30 K [W]	50 K [W]	70 K [W]
Solacept FK22 AR	2.01	1 933	1 163	110	2.25	1 676	1 602	1 435	1 245	1 032

Collector efficiency parameters related to aperture area (Aa) Type of fluid and flow rate see note 1	η_{0a}	0.833	-
	a_{1a}	3.55	W/(m²K)
	a_{2a}	0.0146	W/(m²K²)
Stagnation temperature - Weather conditions see note 2	t_{stg}	208	°C
Effective thermal capacity	$c_{eff} = C/A_a$	5.5	kJ/(m²K)
Max. operation pressure - see note 3	p_{max}	1000	kPa

Incidence angle modifiers $K_\theta(\theta)$			θ_T / θ_L	50°			
	$K_{\theta d}$	0.86	$K_\theta(\theta)$	0.94	at G_{DIF}/G_{TOT}	0.15	
	b_0	0.13					

Testing Laboratory	Institut für Solarenergieforschung Hameln
Website	www.isfh.de
Test report id. number	05-12/KD, 131-09/KQ
Date of test report	17.01.2012, 26.10.2009
Perf. test method	EN 12975-2 6.1.5 (indoor)

Comments of testing laboratory :

The incidence angle modifier was determined outdoor according to a quasi-dynamic test procedure.
The collector efficiency parameter and incidence angle modifiers are related to a radiation ratio of G(Diffuse)/G(Total)=0.15.

Note 1	**Fluid**	Water	**Flow rate**	0.041	kg/s per m²
Note 2	**Irradiance, Gs=1000 W/m²; Ambient temperature , Ta=30 °C**				
Note 3	**Given by manufacturer**				

ISFH
Institut für Solarenergieforschung GmbH
Am Ohrberg 1
D-31860 Emmerthal
Tel.: 0 51 51 / 999-100
Fax: 0 51 51 / 999-500

VERSION 3.6, 2012.01.20

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence number	011-7S671 F
	Issued	14.04.2015

Annual collector output kWh

Collector name	Location and collector temperature (Tm)														
	Athens			Davos			Stockholm			Würzburg					
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C			
Solacept FK22 AR	2 652	1 937	1 299	2 190	1 541	982	1 499	1 006	625	1 626	1 086	664			

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). Detailed description with all equations used is available from the Solar Keymark web site (direct link: http://www.estif.org/solarkeymark/annexb1.php)

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin
Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de

Datasheet version:
VERSION 3.6, 2012.01.20
Calculation program version:
3.07, October 2011 (SP)