

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	TSU 003-10
	Issued	16.11.2015

Annual collector output kWh/module														
Collector name	Location and collector temperature (T _m)													
	Athens			Davos			Stockholm			Würzburg				
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C		
VK/UT-15	2 130	1 895	1 606	1 819	1 564	1 284	1 326	1 119	898	1 427	1 208	971		
VK/UT-10	1 415	1 259	1 067	1 209	1 039	853	881	744	597	948	802	645		

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)
--	--

Overview of locations				
Location	Latitude °	G _{tot} kWh/m ²	T _a °C	Collector orientation or tracking mode
Athens	38	1 765	18,5	South, 25°
Davos	47	1 714	3,2	South, 30°
Stockholm	59	1 166	7,5	South, 45°
Würzburg	50	1 244	9,0	South, 35°

G _{tot}	Annual total irradiation on collector plane	kWh/m ²
T _a	Mean annual ambient air temperature	°C
T _m	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (T_m). A detailed description of the calculations is available at <http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx>.

Technický skúšobný ústav Piešťany, š.p. Address: Krajinská cesta 2929/9, 92101 Piešťany, Slovak Republic Phone: +421 33 79 57 111, Fax: +421 33 77 23 716, E-mail: sv@tsu.sk, web: www.tsu.eu	Datasheet version: 4.06, 2014-01-15
	ScenoCalc version: Ver. 4.06 (Jan, 2014)