



Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S2644 F
	Date of issue	19.04.2016

Company	Riello NV/SA	Country	Belgium
Brand (optional)	--	Website	www.riello.be
Street, number	Waverstraat 15	E-mail	info@riello.be
Postal Code	BE-9310	Tel.	+32 53 769 030
City	Moorsel (Aalst)	Fax	+32 53 789 440

Collector Type (flat plate / evacuate tubular / un-glazed)	Flat plate collector
------------------------------------------------------------	--------------------------------------

Integration in the roof possible ?	No
------------------------------------	----

Collector name	Aperture area (A _a) [m ²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (A _G) [m ²]	Power output per collector unit G = 1000 W/m ² T _m -T _a :				
						0 K	10 K	30 K	50 K	70 K
						[W]	[W]	[W]	[W]	[W]
CSAO 25 R	2.284	1'240	2'078	100	2.577	1'809	1'732	1'564	1'377	1'173

Collector efficiency parameters related to <u>aperture area (A_a)</u> Type of fluid and flow rate see note 1	η _{0a}	0.792	-
	a _{1a}	3.28	W/(m ² K)
	a _{2a}	0.0100	W/(m ² K ²)

Stagnation temperature - Weather conditions see note 2	t _{stg}	214	°C
--------------------------------------------------------	------------------	-----	----

Effective thermal capacity	C _{eff} = C/A _a	5.9	kJ/(m ² K)
----------------------------	-------------------------------------	-----	-----------------------

Max. operation pressure - see note 3	p _{max}	1000	kPa
--------------------------------------	------------------	------	-----

Incidence angle modifiers K _θ (θ)	G _{DIF} /G _{TOT}		θ _T / θ _L	50°	10°	20°	30°	40°	60°	70°
	min	max								
	G _{DIF} /G _{TOT} : min&max - while measuring	0.11	0.17	K _θ (θ _L)	0.86	1.00	1.00	0.99	0.94	0.76
				0.86	1.00	1.00	0.99	0.94	0.76	0.56

Optional values

Testing Laboratory	SPF, CH-8640 Rapperswil
Website	www.spf.ch
Test report id. number	C1696LPEN, C1696QPEN
Date of test report	31.03.2016/31.03.2016
Perf. test method	EN 12975-2 6.1.4 (outdoor)

Comments of testing laboratory :	

Note 1	Fluid	Water-Glycole	Flow rate	0.023 kg/s per m ²	Dr. Andreas Bohren
Note 2	Irradiance, G _s =1000 W/m ² Ambient temperature, T _a =30 °C				
Note 3	Given by manufacturer				



Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S2644 F
	Issued	19.04.2016

Annual collector output kWh												
Collector name	Location and collector temperature (Tm)											
	Athens			Davos			Stockholm			Würzburg		
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
CSAO 25 R	2'767	2'044	1'419	2'288	1'650	1'118	1'568	1'078	707	1'695	1'156	746

Collector mounting: Fixed or tracking Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations				
Location	Latitude °	Gtot kWh/m ²	Ta °C	Collector orientation or tracking mode
Athens	38	1'765	18.5	South, 25°
Davos	47	1'714	3.2	South, 30°
Stockholm	59	1'166	7.5	South, 45°
Würzburg	50	1'244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m ²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). Detailed description with all equations used is available from the Solar Keymark web site (direct link: <http://www.estif.org/solarkeymark/annexb1.php>)

DIN CERTCO • Alboinstraße 56 • 12103 Berlin Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de	Datasheet version: VERSION 3.5, 2012.01.13 Calculation program version: 3.07, October 2011 (SP)
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------