



Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	OEM 9926/3/1
	Date of issue	15/1/2014

Company	ECA TECHNOLOGY SpA	Country	Italy
Brand (optional)		Website	www.ecatech.it
Street, number	Via Dell'Industria 51	E-mail	eca@ecatech.it
Postal Code	36040	Tel.	+039 0444 418330
City	Grisignano di Zocco	Fax	+039 0444 418355

Collector Type (flat plate / evacuate tubular / un-glazed)	Flat plate collector
---	----------------------

Integration in the roof possible ?	Yes
---	-----

Collector name	Aperture area (Aa) [m ²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (Ag) [m ²]	Power output per collector unit G = 1000 W/m ² Tm-Ta :				
						0 K	10 K	30 K	50 K	70 K
						[W]	[W]	[W]	[W]	[W]
ESPS210	1,80	2.050	1.010	90	2,07	1.332	1.241	1.045	830	597
ESPS260	2,33	2.050	1.280	90	2,62	1.724	1.606	1.352	1.074	772

Collector efficiency parameters related to aperture area (Aa) Note 1	η_{0a}	0,74	-
	a_{1a}	4,94	W/(m ² K)
	a_{2a}	0,0128	W/(m ² K ²)

Stagnation temperature - Note 2	tstg	135,40 °C
--	------	-----------

Effective thermal capacity	C _{eff} = C/A _a	11,9 kJ/(m ² K)
-----------------------------------	-------------------------------------	----------------------------

Max. operation pressure - Note 3	p _{max}	700 kPa
---	------------------	---------

Incidence angle modifiers K _θ (θ)	G _{DIF} /G _{TOT}		θ _T / θ _i	50°	10°	20°	30°	40°	60°	70°
	min	max								
	G _{DIF} /G _{TOT} : min&max - while measuring			K _θ (θ _L)	0,89	1,00	1,00	0,98		0,79

Testing Laboratory	Demokritos
Website	www.solar.demokritos.gr
Test report id. number	1213DE1L, 1214DE1S, 4118DQ1
Date of test report	30/7/2012
Perf. test method	EN 12975-2 6.1.4 (outdoor/außen/extérieur)

Comments of testing laboratory :
[Example data sheet](#)

Note 1	Test conditions	Fluid	Water	Flow rate	0,20	kg/s per m ²	Stamp & signature of test lab
Note 2	Irradiance, G _s =1000 W/m ² Ambient temperature, T _a =30 °C						
Note 3	Given by manufacturer						



Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	OEM 9926/3/1
	Issued	15/1/2014

Annual collector output kWh / Jährliche Kollektor Leistung kWh / Energie annuelle produite par le capteur															
Collector name	Location and collector temperature (T _m)														
	Athens			Davos			Stockholm			Würzburg					
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
ESPS210	2.288	1.494	871	1.790	1.134	643	1.189	692	345	1.318	765	396			
ESPS260	2.962	1.934	1.128	2.317	1.468	833	1.539	895	446	1.706	990	513			

Collector mounting: Fixed or tracking / Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations				
Location	Latitude °	G _{tot} kWh/m ²	T _a °C	Collector orientation or tracking mode
Athens	38	1.765	18,5	South, 25°
Davos	47	1.714	3,2	South, 30°
Stockholm	59	1.166	7,5	South, 45°
Würzburg	50	1.244	9,0	South, 35°

G _{tot}	Annual total irradiation on collector plane	kWh/m ²
T _a	Mean annual ambient air temperature	°C
T _m	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (T_m). Detailed description with all equations used is available from the Solar Keymark web site (direct link: <http://www.estif.org/solarkeymark/annexb1.php>)

Central Offices: Dragoumi 6, 145 61 kifisia, Athens, Tel: +301 6233493-4 , Fax: +301 6233495, http://www.dqshellas.gr, e-mail: ioannisalexiou@dqshellas.gr	Datasheet version: VERSION 3.4, 30-11-2011 Calculation program version: 3.07 October 2011
--	--