




Annex to Solar Keymark Certificate - Summary of EN ISO 9806:2013 Test Results						Licence Number		OEM 9965/1/2																	
						Date issued		2016-11-15																	
						Issued by		DQS Hellas																	
Licence holder			FONDERIE SIME SpA			Country		Italy																	
Brand (optional)						Web		http://www.sime.it/																	
Street, Number			27, Via Garbo			E-mail		info@sime.it																	
Postcode, City			37045, Legnano (VR)			Tel		+390 442 631111																	
Collector Type						Flat plate collector, glazed																			
Collector name						Gross area (A_G)		Gross length		Gross width		Gross height		Power output per collector G _b = 850 W/m ² ; G _d = 150 W/m ² ϑ _m - ϑ _a											
						m ²		mm		mm		mm		0 K		10 K		30 K		50 K		70 K		50 K	
						W		W		W		W		W		W		W							
SIMESOL 132						1,52		1.510		1.010		110		1.053		991		859		716		563		716	
SIMESOL 182						2,03		2.010		1.010		110		1.406		1.323		1.147		957		753		957	
SIMESOL 230						2,53		2.010		1.270		110		1.752		1.649		1.429		1.192		938		1.192	
Power output per m² gross area						693		652		565		471		371		471									
Performance parameters test method						Steady state - outdoor																			
Performance parameters (related to AG)						η _{0,hem}		a ₁		a ₂															
Units						-		W/(m ² K)		W/(m ² K ²)															
Test results						0,693		3,999		0,009															
Incidence angle modifier test method						Steady state - outdoor																			
Bi-directional incidence angle modifiers						No																			
Incidence angle modifier						Angle		10°		20°		30°		40°		50°		60°		70°		80°		90°	
Transversal						K _{θT, coll}		1,00		0,99		0,98		0,97		0,94		0,90		0,81				0,00	
Longitudinal						K _{θL, coll}		1,00		0,99		0,98		0,97		0,94		0,90		0,81				0,00	
Heat transfer medium for testing						Water																			
Flow rate for testing (per gross area, A_G)						dm/dt		0,020																	
Maximum temperature difference for thermal performance calculations						(ϑ _m -ϑ _a) _{max}		50																	
Standard stagnation temperature (G = 1000 W/m²; ϑ_a = 30 °C)						ϑ _{stg}		174																	
Effective thermal capacity, incl. fluid (per gross area, A_G)						C/m ²		7,86																	
Maximum operating temperature						ϑ _{max, op}		100																	
Maximum operating pressure						P _{max, op}		1000																	
Testing laboratory						NCSR Demokritos						www.solar.demokritos.gr													
Test report(s)						4188DE1 4189DE1 4023DQ2, 4046DQ2						Dated		27/7/2016 27/7/2016 05/9/2013											
Comments of testing laboratory						This data sheet was issued based on data appeared in the first SKM certificate.						Datashet version: 5.01, 2016-03-01 													
Central Offices: Kalavriton 4, 145 64 kifisia, Athens, Tel: +301 6233493-4 , Fax: +301 6233495, http://www.dqshellas.gr, e-mail: ioannisalexou@dqshellas.gr																									



Annex to Solar Keymark Certificate Supplementary Information	Licence Number	OEM 9965/1/2
	Issued	2016-11-15

Annual collector output in kWh/collector at mean fluid temperature ϑ_m , based on ISO 9806:2013 test results													
Collector name	Standard Locations ϑ_m	Athens			Davos			Stockholm			Würzburg		
		25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
SIMESOL 132		1.667	1.118	683	1.222	798	469	907	557	315	989	600	334
SIMESOL 182		2.226	1.493	913	1.632	1.066	626	1.211	744	420	1.321	801	446
SIMESOL 230		2.775	1.860	1.137	2.034	1.328	781	1.509	927	524	1.646	998	556
Annual output per m ² gross area		1.097	735	450	804	525	309	597	366	207	651	395	220
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1714 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18,5°C			3,2°C			7,5°C			9,0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 5.01 (March 2016). A detailed description of the calculations is available at www.solarkeymark.org/scenocalc													

Additional Information		
Collector heat transfer medium	Water-Glycole	
Hybrid Thermal and Photo Voltaic collector	No	
The collector is deemed to be suitable for roof integration	No	
The collector was tested successfully according to EN ISO 9806:2013 under the following conditions:		
Climate class (A, B or C)	A	--
Maximum tested positive load	1000	Pa
Maximum tested negative load	1000	Pa
Hail resistance using steel ball (maximum drop height)	-	m

Energy Labelling Information			
	Reference Area, A _{sol} (m ²)	Data required for CDR (EU) No 811/2013 - Reference Area A _{sol}	
APOLLON AL 1500	1,52	Collector efficiency (η_{col})	52 %
APOLLON AL 2000	2,03	<i>Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m², expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2013.</i>	
APOLLON AL 2600	2,53		
		Data required for CDR (EU) No 812/2013 - Reference Area A _{sol}	
		Zero-loss efficiency (η_0)	0,693 --
		First-order coefficient (a ₁)	4,00 W/(m ² K)
		Second-order coefficient (a ₂)	0,009 W/(m ² K ²)
		Incidence angle modifier IAM (50°)	0,94 --
<i>Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.</i>			