



Annex to Solar Keymark Certificate - Summary of EN ISO 9806:2013 Test Results					Licence Number		SKM 10000							
					Date issued		2016-11-30							
					Issued by		DQS Hellas							
Licence holder		BNS PRODUCTION FOOD			Country		BULGARIA							
Brand (optional)					Web		www.bns-production.com							
Street, Number		North Industrial Zone			E-mail		info@bns-production.com							
Postcode, City		3700, Vidin			Tel		+359 878788664							
Collector Type					Evacuated tubular collector									
					Power output per collector									
					Gb = 850 W/m ² ; Gd = 150 W/m ² θ _m - θ _a									
					0 K	10 K	30 K	50 K	70 K	52 K				
Collector name					m ²	mm	mm	mm	W	W	W	W	W	W
Sunfective 8					1.68	2,000	840	135	748	718	653	578	494	570
Sunfective 9					1.91	2,000	953	135	850	817	742	657	561	648
Sunfective 10					2.13	2,000	1,067	135	948	911	828	733	626	723
Sunfective 11					2.36	2,000	1,180	135	1,050	1,009	917	812	693	801
Sunfective 12					2.59	2,000	1,294	135	1,153	1,107	1,006	891	761	879
Sunfective 13					2.81	2,000	1,407	135	1,250	1,202	1,092	967	826	953
Sunfective 14					3.04	2,000	1,520	135	1,353	1,300	1,181	1,046	893	1,031
Sunfective 15					3.27	2,000	1,634	135	1,455	1,398	1,271	1,125	961	1,109
Sunfective 16					3.50	2,000	1,750	135	1,558	1,497	1,360	1,204	1,028	1,187
Sunfective 17					3.72	2,000	1,861	135	1,655	1,591	1,446	1,280	1,093	1,262
Sunfective 18					3.95	2,000	1,974	135	1,758	1,689	1,535	1,359	1,161	1,340
Sunfective 19					4.18	2,000	2,088	135	1,860	1,787	1,624	1,438	1,228	1,418
Sunfective 20					4.40	2,000	2,201	135	1,958	1,881	1,710	1,514	1,293	1,493
Sunfective 21					4.63	2,000	2,314	135	2,060	1,980	1,799	1,593	1,360	1,571
Sunfective 22					4.86	2,000	2,428	135	2,163	2,078	1,889	1,672	1,428	1,649
Sunfective 23					5.08	2,000	2,541	135	2,261	2,172	1,974	1,748	1,493	1,723
Power output per m ² gross area					445	428	389	344	294	339				
Performance parameters test method					Steady state - outdoor									
Performance parameters (related to AG)					η _{0,hem}	a ₁	a ₂							
Units					-	W/(m ² K)	W/(m ² K ²)							
Test results					0.445	1.670	0.007							
Incidence angle modifier test method					Quasi dynamic - outdoor									
Bi-directional incidence angle modifiers					Yes									
Incidence angle modifier					Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
Transversal					K _{θT, coll}					1.01			0.00	
Longitudinal					K _{θL, coll}					0.88			0.00	
Heat transfer medium for testing					Water									
Flow rate for testing (per gross area, A _G)					dm/dt	0.020	kg/(sm ²)							
Maximum temperature difference for thermal performance calculations					(θ _m -θ _a) _{max}	52	K							
Standard stagnation temperature (G = 1000 W/m ² ; θ _a = 30 °C)					θ _{stg}	190	°C							
Effective thermal capacity, incl. fluid (per gross area, A _G)					C/m ²	6.7	kJ/(Km ²)							
Maximum operating temperature					θ _{max op}	-	°C							
Maximum operating pressure					p _{max,op}	600	kPa							
Testing laboratory		NCSR Demokritos / Solar & other Energy Systems Laboratory			www.solar.demokritos.gr									
Test report(s)		4180 DE4 4181 DE4 4181 DQ4			Dated		1/2/2017 1/2/2017 1/2/2017							
Comments of testing laboratory					Datasheet version: 5.01, 2016-03-01									
The effective thermal capacity value was obtained from the Test Report Nr. 04-17/KT dated 30.01.2017 issued by Institut für Solarenergieforschung GmbH .					N.C.S.R "DEMOKRITOS" SOLAR ENERGY LABORATORY Head: Dr Vassilis Belesiotis Tel: +210 6503815 - Fax: +210 6544524 153 10 Ag. Paraskevi - Attiki - Greece									
Central Offices: Kalavriton 4, 145 64 kifisia, Athens, Tel: +301 6233493-4 , Fax: +301 6233495, http://www.dqshellas.gr, e-mail: ioannisalexidou@dqshellas.gr														



Annex to Solar Keymark Certificate Supplementary Information	Licence Number	SKM 10000
	Issued	2016-11-30

Annual collector output in kWh/collector at mean fluid temperature ϑ_m , based on ISO 9806:2013 test results

Collector name	Standard Locations ϑ_m	Athens			Davos			Stockholm			Würzburg		
		25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
Sunfective 8		1,141	859	603	899	660	454	655	460	306	706	492	322
Sunfective 9		1,297	977	685	1,022	751	517	745	523	348	803	559	366
Sunfective 10		1,447	1,089	764	1,140	837	576	831	583	388	895	623	408
Sunfective 11		1,603	1,207	847	1,263	928	638	920	646	429	992	691	452
Sunfective 12		1,759	1,324	929	1,386	1,018	700	1,010	709	471	1,089	758	496
Sunfective 13		1,909	1,437	1,008	1,503	1,105	760	1,096	769	511	1,181	822	538
Sunfective 14		2,065	1,554	1,091	1,627	1,195	822	1,185	832	553	1,278	890	582
Sunfective 15		2,221	1,672	1,173	1,750	1,285	884	1,275	895	595	1,375	957	626
Sunfective 16		2,377	1,790	1,256	1,873	1,376	947	1,365	958	637	1,471	1,024	671
Sunfective 17		2,527	1,902	1,335	1,990	1,462	1,006	1,451	1,018	677	1,564	1,089	713
Sunfective 18		2,683	2,020	1,417	2,113	1,553	1,068	1,540	1,081	719	1,661	1,156	757
Sunfective 19		2,839	2,137	1,500	2,236	1,643	1,130	1,630	1,144	761	1,757	1,223	801
Sunfective 20		2,989	2,250	1,579	2,354	1,730	1,190	1,716	1,205	801	1,850	1,288	843
Sunfective 21		3,145	2,367	1,661	2,477	1,820	1,252	1,805	1,267	842	1,946	1,355	887
Sunfective 22		3,301	2,485	1,744	2,600	1,911	1,314	1,895	1,330	884	2,043	1,422	931
Sunfective 23		3,451	2,598	1,823	2,718	1,997	1,374	1,981	1,391	924	2,136	1,486	973
Annual output per m ² gross area		679	511	359	535	393	270	390	274	182	420	293	192
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1714 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 5.01 (March 2016). A detailed description of the calculations is available at www.solarkeymark.org/scenocalc

Additional Information

Collector heat transfer medium	Water-Glycole	
Hybrid Thermal and Photo Voltaic collector	No	
The collector is deemed to be suitable for roof integration	No	
The collector was tested successfully according to EN ISO 9806:2013 under the following conditions:		
Climate class (A, B or C)	A	--
Maximum tested positive load	2400	Pa
Maximum tested negative load	na	Pa
Hail resistance using steel ball (maximum drop height)	0.4	m

Energy Labelling Information

	Reference Area, A_{sol} (m ²)	Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}			
Sunfective 8	1.68	Collector efficiency (η_{col})	37 %		
Sunfective 9	1.91	<i>Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m², expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2013.</i>			
Sunfective 10	2.13				
Sunfective 11	2.36				
Sunfective 12	2.59				
Sunfective 13	2.81				
Sunfective 14	3.04				
Sunfective 15	3.27				
Sunfective 16	3.50				
Sunfective 17	3.72			Zero-loss efficiency (η_0)	0.445 --
Sunfective 18	3.95			First-order coefficient (a_1)	1.67 W/(m ² K)
Sunfective 19	4.18	Second-order coefficient (a_2)	0.007 W/(m ² K ²)		
Sunfective 20	4.40	Incidence angle modifier IAM (50°)	0.00 --		
Sunfective 21	4.63	<i>Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.</i>			
Sunfective 22	4.86				
Sunfective 23	5.08				