

KEYMARK CERTIFICATE

SK08055371501/R01

TUV CYPRUS LTD Certifies that the organization

THERMOSIFONES KAFSON LTD

Address: Arch. Makariou III 125,
8310 Koloni, (Paphos), CYPRUS

Supplies: Solar thermal collectors

In compliance with: EN 12975-1:2006+A1:2010 & EN 12975-2:2006

Certified Product: Solar Collector

Trade Mark: KCSA/D 1.5 SKM, KCSA/D 2.0 SKM

Test Results: Annex to certificate

Certification scheme: The initial Certificate with number 081BN/0 of Solar Keymark Certification Body CEN025 was issued on 27/09/2011. In order to grant this certificate, TUV CYPRUS has visited the manufacturing site and verified the implementation of the quality management system. TUV CYPRUS performs these tasks periodically while the certificate has not been cancelled, in accordance with the Product Certification Regulations and the Rules for Authorization to use Conformity Mark for Solar Collectors.



TUV CYPRUS (TUV NORD) LTD
Certification Body

Nicosia , 05/06/2015
Initial Certification : 27/09/2011
Valid until : 15/03/2020



SOLAR KEYMARK
CERTIFICATION BODY
CEN 033

Accredited by





Certificate No. 885





CEN 033

Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate						Licence Number		SK08055371501/R01			
						Issued		2015-05-06			
Company holding the		THERMOSIFONES KAFSON LTD				Country		CYPRUS			
Brand (optional)						Website		www.kafson.com			
Street, street number		Archiepiskopou Makariou III 125, KOLONI				E-mail		info@kafson.com			
Postal Code / City, province		8310 PAPHOS				Tel/Fax		357 70008182			
Collector Type (flat plate glazed/un-glazed; evacuate tubular)						Flat plate collector - glazed					
Thermal / photo voltaic hybrid collector? (PVT collector)						No					
Integration in the roof possible ? (manufacturers declaration)						No					
Collector name	Aperture area (Aa) m ²	Gross length mm	Gross width mm	Gross height mm	Gross area (AG) m ²	Power output per collector module					
						G = 1000 W/m ²					
						Tm-Ta					
						0 K	10 K	30 K	50 K	70 K	
						W	W	W	W	W	
KCSA/D 2.0 SKM	1.83	2,000.00	1,000.00	85	2.00	1,363	1,289	1,084	807	456	
KCSA/D 1.5 SKM	1.35	1,500.00	1,000.00	85	1.50	1,006	951	800	595	337	
Performance test method						Glazed liquid heating collector - steady state - indoor					
Performance parameters related to aperture		η_0	a1	a2							
Units		-	W/(m ² K)	W/(m ² K ²)							
Test results - Flow rate and fluid see note 1		0.745	3.580	0.050							
Bi-directional incidence angle modifiers? No		K θ values are obligatory for 50°.									
Incidence angle modifiers K θ (θ)		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
		K θ (θ)					0.95				0.00
Incidence angle modifier not bi-directional - leave fields blank											
Stagnation temperature - Weather conditions see note 2						Tstg	132.9 °C				
Effective thermal capacity						ceff = C/Ag	16.3 kJ/(m ² K)				
Max. intended operation temperature - see note 3						Tmax,op	133 °C				
Max. operation pressure - see note 3						pmax,op	600 kPa				
Pressure drop table - for a collector family, the values shall be for the module with highest ΔP per m ² aperture area											
Flow rate	kg/(s m ²)	0.000	0.051	0.081	0.102	0.117	0.127				
Pressure drop, ΔP	Pa	0	40	70	90	110	130				
Optional weather data		Location			Link						
Testing Laboratory		ISTITUTO GIORDANO									
Website		www.giordano.it									
Test report id. number		283543, 283544				Date of test report		2011/06/16			
During the test GDIF/GTOT was always between		-	and	-							
Comments of testing laboratory:											
Note 1	Flow rate	0.037 kg/(s m ²)	Fluid	Water							
Note 2	Irradiance, G = 1000 W/m ² ; Ambient temperature, Ta=30 °C										
Note 3	Given by manufacturer										
						 Datasheet version: 4.06, 2014-01-15					
TUV CYPRUS LTD						e-mail: info@tuvcyprus.com.cy					
P.O.Box: 20732						www.tuv-nord.com/cy					
Nicosia 1663, CYPRUS											
Phone: +35722442840, Fax : +35722442850											



CEN 033

Page 2/2

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	SK08055371501/R01
	Issued	2015-05-06

Annual collector output kWh/module												
Collector name	Location and collector temperature (Tm)											
	Athens			Davos			Stockholm			Würzburg		
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
KCSA/D 2.0 SKM	2,178	1,401	656	1,588	895	331	1,193	654	251	1,301	707	272
KCSA/D 1.5 SKM	1,607	1,034	484	1,171	661	244	880	483	185	960	522	200

Collector mounting: Fixed or tracking Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations				
Location	Latitude °	Gtot kWh/m ²	Ta °C	Collector orientation or tracking mode
Athens	38	1,765	18.5	South, 25°
Davos	47	1,714	3.2	South, 30°
Stockholm	59	1,166	7.5	South, 45°
Würzburg	50	1,244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m ²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). A detailed description of the calculations is available at <http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx>.