

Number	15707 Rev.0	Replaces	-
Issued	09/05/2018	First edition	09/05/2018
Report number	PKC0002092	Expiry date	08/05/2023
Page	1 of 1	Contract number	PKC0002751

Product Certificate Solar Thermal Products

Kiwa Cermet Italia hereby declares that the **solar thermal collector**, type

BLUh+

supplied by **Sunerg Solar S.r.l.**
Via Donino Donini 51 - 06012 Cinquemiglia - Città di Castello (PG), Italy

Is entitled to use the Solar Keymark label.

The compliance is based on examination to:
ISO 9806:2013 and the
Specific Keymark Scheme Rules for Solar Thermal Products V31.00

A description of the test results is given in the appendix to this certificate.

*This certificate is issued in accordance with the Kiwa Cermet Italia regulations.
Publication of the certificate is allowed.
The validity of this certificate is subject to the positive result of periodic surveillance visits.*

Chief Operating Officer
Giampiero Belcredi



Kiwa Cermet Italia S.p.A.

Società con socio unico, soggetta all'attività di direzione e coordinamento di Kiwa Italia Holding Srl

Via Cadriano, 23
40057 Granarolo dell'Emilia (BO)

Unità secondaria

Via Treviso 32/34
31020 San Vendemiano (TV)

Tel +39. 0438 411755

Fax +39.0438 22428


E-mail: info@kiwacermet.it

www.kiwa.it

www.kiwacermet.it



SGQ N° 007A
SGA N° 010D
PRD N° 069B
FSM N° 004I
PRS N° 089C

Annex to Solar Keymark Certificate - Summary of EN ISO 9806:2013 Test Results					Licence Number		15707 Rev.0							
					Date issued		2018-05-09							
					Issued by		Kiwa Cermet Italia S.p.A.							
Licence holder		Sunerg Solar S.r.l.			Country		Italy							
Brand (optional)					Web		http://www.sunergsolar.com							
Street, Number		Via Donino Donini 51			E-mail		info@sunergsolar.com							
Postcode, City		06012 Città di Castello (PG)			Tel		+39 0758540018							
Collector Type					Flat plate collector, glazed									
Collector name					Gross area (A _G)	Gross length	Gross width	Gross height	Power output per collector G _b = 850 W/m ² ; G _d = 150 W/m ² ̑ _m - ̑ _a					
					m ²	mm	mm	mm	0 K	10 K	30 K	50 K	70 K	64 K
BLUhx+					2.52	1,987	1,270	100	2,008	1,926	1,750	1,557	1,349	1,413
Power output per m ² gross area					797	764	694	618	535	561				
Performance parameters test method					Steady state - outdoor									
Performance parameters (related to AG)					̑ _{0,hem}	a1	a2							
Units					-	W/(m ² K)	W/(m ² K ²)							
Test results					0.797	3.180	0.008							
Incidence angle modifier test method					Steady state - outdoor									
Bi-directional incidence angle modifiers					No									
Incidence angle modifier					Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
Transversal					K _{gT, coll}									
Longitudinal					K _{gL, coll}									
Heat transfer medium for testing					Water									
Flow rate for testing (per gross area, A _G)					dm/dt		0.019	kg/(sm ²)						
Maximum temperature difference for thermal performance calculations					(̑ _m -̑ _a) _{max}		64	K						
Standard stagnation temperature (G = 1000 W/m ² ; ̑ _a = 30 °C)					̑ _{stg}		224	°C						
Effective thermal capacity, incl. fluid (per gross area, A _G)					C/m ²		10.2	kJ/(Km ²)						
Maximum operating temperature					̑ _{max, op}		185	°C						
Maximum operating pressure					p _{max, op}		600	kPa						
Testing laboratory		ENEA - Centro Ricerche Trisaia			http://www.trisaia.enea.it									
Test report(s)		RP.2018.COL.198.1			Dated		09/05/2018							
Comments of testing laboratory					Datasheet version: 5.01, 2016-03-01									
					ENEA DTE-STT Dr. Vincenzo Sabatelli 									
Kiwa Cermet Italia S.p.A. • Via Cadriano, 23 • 40057 Granarolo dell'Emilia (BO) • Italy Tel: +39 0514593111 • Fax: +39 051763382 • E-Mail: info@kiwacermet.it • www.kiwacermet.it														



Annex to Solar Keymark Certificate Supplementary Information	Licence Number	15707 Rev.0
	Issued	2018-05-09

Annual collector output in kWh/collector at mean fluid temperature ϑ_m , based on ISO 9806:2013 test results													
Collector name	Standard Locations ϑ_m	Athens			Davos			Stockholm			Würzburg		
		25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
BLUhx+		3,258	2,473	1,786	2,554	1,899	1,340	1,869	1,319	894	2,025	1,428	951
Annual output per m ² gross area		1,293	981	709	1,014	754	532	742	524	355	804	567	378
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1714 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 5.01 (March 2016). A detailed description of the calculations is available at www.solarkeymark.org/scenocalc

Additional Information		
Collector heat transfer medium	Water-Glycole	
Hybrid Thermal and Photo Voltaic collector	No	
The collector is deemed to be suitable for roof integration	Yes	
The collector was tested successfully according to EN ISO 9806:2013 under the following conditions:		
Climate class (A, B or C)	A	--
Maximum tested positive load	2410	Pa
Maximum tested negative load	2006	Pa
Hail resistance using steel ball (maximum drop height)	2	m

Energy Labelling Information			
	Reference Area, A_{sol} (m ²)	Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}	
BLUhx+	2.52	Collector efficiency (η_{col})	66 %
		<i>Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m², expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2013.</i>	
		Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}	
		Zero-loss efficiency (η_0)	0.797 --
		First-order coefficient (a_1)	3.18 W/(m ² K)
		Second-order coefficient (a_2)	0.008 W/(m ² K ²)
		Incidence angle modifier IAM (50°)	0.95 --
		<i>Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.</i>	

Kiwa Cermet Italia S.p.A. • Via Cadrano, 23
 • 40057 Granarolo dell'Emilia (BO) • Italy
 Tel: +39 0514593111 • Fax: +39 051763382 • E-Mail: info@kiwacermet.it • www.kiwacermet.it