

Annex to Solar Keymark Certificate Supplementary Information	Licence Number	011-7S2948 P
	Issued	2019-09-19

Annual collector output in kWh/collector at mean fluid temperature ϑ_m													
Standard Locations		Athens			Davos			Stockholm			Würzburg		
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
KI 280 H		720	56	0	259	4		257	10		305	17	
Annual output per m ² gross area		431	33	0	155	3		154	6		183	10	
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1714 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18,5°C			3,2°C			7,5°C			9,0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.0 (October 2018). A detailed description of the calculations is available at www.solarkeymark.org/scenocalc

Additional Information			
Collector heat transfer medium	Water-Glycole		
The collector is deemed to be suitable for roof integration	No		
The collector was tested successfully under the following conditions:			
Climate class (A+, A, B or C)	A		--
G (W/m ²) >	1000	ϑ_a (°C) >	20
		H_x (MJ/m ²) >	600
Maximum tested positive load	5400		Pa
Maximum tested negative load	3000		Pa
Hail resistance using steel ball (maximum drop height)	25		m

Additional collector attribute(s)			
<input type="checkbox"/>	Using external power source(s) for normal operation	<input type="checkbox"/>	Active or passive measure(s) for self-protection
<input checked="" type="checkbox"/>	Co-generating thermal and electrical power	<input checked="" type="checkbox"/>	Wind and/or infrared sensitive collector(s) (WISC)
<input type="checkbox"/>	Façade collector(s)		

Energy Labelling Information				
	Reference Area, A_{sol} (m ²)	Hydraulic Designation Code		
KI 280 H	1,67	10-V-1234S-A:7.2,1578-C:16.4,1004		
Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}		Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}		
Collector efficiency (η_{col})	-6%	Zero-loss efficiency (η_0)	0,34	
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		First-order coefficient (a_1)	8,37	
		Second-order coefficient (a_2)	0,045	
		Incidence angle modifier IAM (50°)	0,89	--
		Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.		