TÜVRheinland®
DIN CERTCO
Precisely Right.

Annex to Solar Keymark Certificate

Licence Number	**011-7S2968 F**
Date issued	**2020-02-19**
Issued by	**TÜV Rheinland Energy GmbH**

Licence holder	**Galécia - Produtos para a Indústria e Construção S.A.**	**Country**	Portugal
Brand (optional)	VICOREN	**Web**	www.galecia.pt
Street, Number	Rua dos Combatentes, 681 Fajozes	**E-mail**	geral@galecia.pt
Postcode, City	4485 – 093 Vila do Conde	**Tel**	+351 252 660 500

Collector Type	Flat plate collector

Collector name	**Gross area (A_G)**	**Gross length**	**Gross width**	**Gross height**	**Power output per collector** Gb = 850 W/m2, Gd = 150 W/m2 & u = 1.3 m/s $\vartheta_m - \vartheta_a$					
					0 K	10 K	30 K	50 K	70 K	100 K
	m²	mm	mm	mm	W	W	W	W	W	W
VICOREN-PLANO P-G/0.8-2m2	2.00	2 000	1 000	95	1 553	1 477	1 314	1 136	944	630
VICOREN-PLANO P-G/0.8-3m2	3.00	3 000	1 500	95	2 329	2 215	1 971	1 704	1 417	944
Power output per m² gross area					776	738	657	568	472	315

Performance parameters test method	Quasi dynamic									
Performance parameters (related to A_G)	η0, b	a1	a2	a3	a4	a5	a6	a7	a8	Kd
Units	-	W/(m²K)	W/(m²K²)	J/(m³K)	-	J/(m²K)	s/m	W/(m²K⁴)	W/(m²K⁴)	-
Test results	0.783	3.72	0.009	0.000	0.00	12 180	0.000	0.00	0.0E+00	0.94

Incidence angle modifier test method		Quasi dynamic - outdoor								
Incidence angle modifier	Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
Transversal	$K_{\theta T,coll}$	1.00	1.00	0.98	0.96	0.93	0.88	0.77	0.00	0.00
Longitudinal	$K_{\theta L,coll}$	1.00	1.00	0.98	0.96	0.93	0.88	0.77	0.00	0.00

Heat transfer medium for testing	Water		
Flow rate for testing (per gross area, A_G)	dm/dt	0.020	kg/(sm²)
Maximum temperature difference during thermal performance test	$(\vartheta_m-\vartheta_a)_{max}$	70	K
Standard stagnation temperature (G = 1000 W/m²; ϑ_a = 30 °C)	ϑ_{stg}	220	°C
Maximum operating temperature	$\vartheta_{max\ op}$	n.n.	°C
Maximum operating pressure	$p_{max,op}$	800	kPa

Testing laboratory	TÜV Rheinland (Shanghai) Co., Ltd.	http://www.tuv.com/solarenergy	
Test report(s)	154150039_Linuo_P-G-2.80_ISO_Report_chen 154150039_Linuo_P-G-1.82_ISO_Report_chen 21249149.010 (Doc-Check)	**Dated**	08.11.2017 09.11.2017 19.02.2020

Comments of testing laboratory

Datasheet version: 6.1, 2019-09-26

TÜVRheinland®
Genau Richtig.
TÜV Rheinland Energy GmbH
Am Grauen Stein
51105 Köln

Annex to Solar Keymark Certificate	Licence Number	011-7S2968 F
Supplementary Information	Issued	2020-02-19

Annual collector output in kWh/collector at mean fluid temperature ϑ_m

Standard Locations		Athens			Davos			Stockholm			Würzburg		
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
VICOREN-PLANO P-G/0.8-2m2		2 489	1 789	1 199	1 897	1 330	865	1 391	925	578	1 519	1 001	615
VICOREN-PLANO P-G/0.8-3m2		3 734	2 683	1 798	2 845	1 995	1 298	2 087	1 388	867	2 278	1 502	923
Annual output per m² gross area		1 245	894	599	948	665	433	696	463	289	759	501	308
Annual efficiency, η_a		71%	51%	34%	58%	41%	27%	60%	40%	25%	61%	40%	25%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m²			1630 kWh/m²			1166 kWh/m²			1244 kWh/m²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature ϑm (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (September 2019). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/

Additional Information

Collector heat transfer medium					Water-Glycole	
The collector is deemed to be suitable for roof integration					No	
The collector was tested successfully under the following conditions:						
Climate class (A+, A, B or C)					C	--
G (W/m²) >	800	ϑ_a (°C) >	10	H_x (MJ/m²) >		600
Maximum tested positive load					2760	Pa
Maximum tested negative load					1888	Pa
Hail resistance using steel ball (maximum drop height)					2	m

Additional collector attribute(s)

- ☐ Using external power source(s) for normal operation
- ☐ Active or passive measure(s) for self-protection
- ☐ Co-generating thermal and electrical power
- ☐ Façade collector(s)

Energy Labelling Information

	Reference Area, A_{sol} (m²)
VICOREN-PLANO P-G/0.8-2m2	2.00
VICOREN-PLANO P-G/0.8-3m2	3.00

Additional Informative Technical Data

	Hydraulic Designation Code	Aperature Area, A_a (m²)
VICOREN-PLANO P-G/0.8-2m2	9-VH-1234S-A:8,1874-C:20,1050	1.85
VICOREN-PLANO P-G/0.8-3m2	14-VH-1234S-A: 8,1874-C:20,1550	2.83

Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}

Collector efficiency (η_{col})	61%

Remark: Collector efficiency (ηcol) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m², expressed in % and rounded to the nearest integer. Deviating from the regulation ηcol is based on reference area (Asol) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.

Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}

Zero-loss efficiency (η_0)	0.78	--
First-order coefficient (a_1)	3.72	W/(m²K)
Second-order coefficient (a_2)	0.009	W/(m²K²)
Incidence angle modifier IAM (50°)	0.92	--

Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin, Germany
Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de