

Annex to Solar Keymark Certificate						Licence Number		011-7S2968 F					
Supplementary Information						Issued		2020-09-02					
Annual collector output in kWh/collector at mean fluid temperature ϑ_m													
Standard Locations		Athens			Davos			Stockholm			Würzburg		
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
VICOREN-PLANO P-G/0.8-2m2		2 489	1 789	1 199	1 897	1 330	865	1 391	925	578	1 519	1 001	615
VICOREN-PLANO P-G/0.8-3m2		3 734	2 683	1 798	2 845	1 995	1 298	2 087	1 388	867	2 278	1 502	923
Annual output per m ² gross area		1 245	894	599	948	665	433	696	463	289	759	501	308
Annual efficiency, η_a		71%	51%	34%	58%	41%	27%	60%	40%	25%	61%	40%	25%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (September 2019). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/													
Additional Information													
Collector heat transfer medium								Water-Glycole					
The collector is deemed to be suitable for roof integration								No					
The collector was tested successfully under the following conditions:													
Climate class (A+, A, B or C)								C		--			
G (W/m ²) >		800		ϑ_a (°C) >		10		H _x (MJ/m ²) >		600			
Maximum tested positive load								2760		Pa			
Maximum tested negative load								1888		Pa			
Hail resistance using steel ball (maximum drop height)								2		m			
Additional collector attribute(s)													
<input type="checkbox"/> Using external power source(s) for normal operation				<input type="checkbox"/> Active or passive measure(s) for self-protection									
<input type="checkbox"/> Co-generating thermal and electrical power				<input type="checkbox"/> Façade collector(s)									
Energy Labelling Information						Additional Informative Technical Data							
		Reference Area, A _{sol} (m ²)		Hydraulic Designation Code			Aperture Area, A _a (m ²)						
VICOREN-PLANO P-G/0.8-2m2		2.00		9-VH-1234S-A:8,1874-C:20,1050			1.85						
VICOREN-PLANO P-G/0.8-3m2		3.00		14-VH-1234S-A: 8,1874-C:20,1550			2.83						
Data required for CDR (EU) No 811/2013 - Reference Area A _{sol}						Data required for CDR (EU) No 812/2013 - Reference Area A _{sol}							
Collector efficiency (η_{col})		61%				Zero-loss efficiency (η_0)		0.78		--			
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.				First-order coefficient (a ₁)		3.72		W/(m ² K)					
				Second-order coefficient (a ₂)		0.009		W/(m ² K ²)					
				Incidence angle modifier IAM (50°)		0.92		--					
		Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.											
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany													
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de													