

<b>Annex to Solar Keymark Certificate - Summary of EN ISO 9806:2013 Test Results</b>					<b>Licence Number</b>		<b>011-7S425 F</b>							
					<b>Date issued</b>		<b>2018-07-11</b>							
					<b>Issued by</b>		<b>DIN CERTCO</b>							
<b>Licence holder</b>	<b>Citrin Solar GmbH</b>				<b>Country</b>	<b>Deutschland</b>								
<b>Brand (optional)</b>					<b>Web</b>	<b>www.citrinsolar.de</b>								
<b>Street, Number</b>	<b>Böhmerwaldstrasse 32</b>				<b>E-mail</b>	<b>info@citrinsolar.de</b>								
<b>Postcode, City</b>	<b>85368 Moosburg</b>				<b>Tel</b>	<b>+49 (0) 8761 3340-0 / (0) 8761 3340-40</b>								
<b>Collector Type</b>					<b>Flat plate collector, glazed</b>									
<b>Collector name</b>	<b>Gross area (A<sub>G</sub>)</b> m <sup>2</sup>	<b>Gross length</b> mm	<b>Gross width</b> mm	<b>Gross height</b> mm	<b>Power output per collector</b> G <sub>b</sub> = 850 W/m <sup>2</sup> ; G <sub>d</sub> = 150 W/m <sup>2</sup> ϑ <sub>m</sub> - ϑ <sub>a</sub>									
					<b>0 K</b> W	<b>10 K</b> W	<b>30 K</b> W	<b>50 K</b> W	<b>70 K</b> W	<b>90 K</b> W				
<b>CS 300</b>	2.02	1 965	1 026	80	1 483	1 405	1 240	1 058	862	651				
<b>CS 350</b>	2.52	2 183	1 153	80	1 850	1 753	1 546	1 320	1 076	812				
<b>Power output per m<sup>2</sup> gross area</b>					<b>734</b>	<b>696</b>	<b>614</b>	<b>524</b>	<b>427</b>	<b>322</b>				
<b>Performance parameters test method</b>					<b>Steady state - indoor</b>									
<b>Performance parameters (related to A<sub>G</sub>)</b>					<b>η<sub>0,hem</sub></b>	<b>a1</b>	<b>a2</b>							
<b>Units</b>					-	W/(m <sup>2</sup> K)	W/(m <sup>2</sup> K <sup>2</sup> )							
<b>Test results</b>					0.734	3.73	0.0094							
<b>Incidence angle modifier test method</b>					<b>Steady state - indoor</b>									
<b>Bi-directional incidence angle modifiers</b>					<b>No</b>									
<b>Incidence angle modifier</b>					<b>Angle</b>	<b>10°</b>	<b>20°</b>	<b>30°</b>	<b>40°</b>	<b>50°</b>	<b>60°</b>	<b>70°</b>	<b>80°</b>	<b>90°</b>
<b>Transversal</b>					K <sub>θT, coll</sub>	1.00	1.00	0.99	0.98	0.95	0.88	0.75	0.49	0.00
<b>Longitudinal</b>					K <sub>θL, coll</sub>	1.00	1.00	0.99	0.98	0.95	0.88	0.75	0.49	0.00
<b>Heat transfer medium for testing</b>					<b>Water</b>									
<b>Flow rate for testing (per gross area, A<sub>G</sub>)</b>					dm/dt	0.044	kg/(sm <sup>2</sup> )							
<b>Maximum temperature difference for thermal performance calculations</b>					(ϑ <sub>m</sub> -ϑ <sub>a</sub> ) <sub>max</sub>	90	K							
<b>Standard stagnation temperature (G = 1000 W/m<sup>2</sup>; ϑ<sub>a</sub> = 30 °C)</b>					ϑ <sub>stg</sub>	195	°C							
<b>Effective thermal capacity, incl. fluid (per gross area, A<sub>G</sub>)</b>					C/m <sup>2</sup>	4.814	kJ/(Km <sup>2</sup> )							
<b>Maximum operating temperature</b>					ϑ <sub>max, op</sub>	130	°C							
<b>Maximum operating pressure</b>					p <sub>max, op</sub>	1000	kPa							
<b>Testing laboratory</b>					<b>TZS, ITW University Stuttgart</b>									
<b>Test report(s)</b>					<b>www.itw.uni-stuttgart.de</b>									
					<b>Dated</b>		<b>26.10.2010, 26.10.2010</b>							
							<b>20.06.2018, 20.06.2018</b>							
<b>Comments of testing laboratory</b>					<b>Datasheet version: 5.01, 2016-03-01</b>									
<p>This data sheet replaces the data sheet issued on 27.10.2016</p> <p>Documented performance parameters are taken from C1355LPEN -SPF, (CS 300)</p> <p>The gross area was changed from 2.53 m<sup>2</sup> to 2.52 m<sup>2</sup></p> <p>The length and width were changing from 2186 x1158 mm to 2183x1153 mm</p>														
<b>DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany</b> <b>Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de</b>														

<b>Annex to Solar Keymark Certificate Supplementary Information</b>	<b>Licence Number</b>	<b>011-7S425 F</b>
	<b>Issued</b>	<b>2018-07-11</b>

Annual collector output in kWh/collector at mean fluid temperature $\vartheta_m$ , based on ISO 9806:2013 test results													
Standard Locations		Athens			Davos			Stockholm			Würzburg		
Collector name	$\vartheta_m$	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
CS 300		2 369	1 665	1 081	1 784	1 224	771	1 314	849	513	1 430	916	545
CS 350		2 956	2 077	1 349	2 226	1 526	962	1 639	1 059	640	1 784	1 143	680
Annual output per m <sup>2</sup> gross area		1 173	824	535	883	606	382	650	420	254	708	454	270
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m <sup>2</sup>			1714 kWh/m <sup>2</sup>			1166 kWh/m <sup>2</sup>			1244 kWh/m <sup>2</sup>		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature $\vartheta_m$ (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 5.01 (March 2016). A detailed description of the calculations is available at <a href="http://www.solarkeymark.org/scenocalc">www.solarkeymark.org/scenocalc</a>													

Additional Information		
Collector heat transfer medium	Water-Glycole	
Hybrid Thermal and Photo Voltaic collector	No	
The collector is deemed to be suitable for roof integration	No	
The collector was tested successfully according to EN ISO 9806:2013 under the following conditions:		
Climate class (A, B or C)	A	--
Maximum tested positive load	2404	Pa
Maximum tested negative load	2404	Pa
Hail resistance using steel ball (maximum drop height)	0.8	m

Energy Labelling Information			
	Reference Area, $A_{sol}$ (m <sup>2</sup> )	Data required for CDR (EU) No 811/2013 - Reference Area $A_{sol}$	
CS 300	2.02	Collector efficiency ( $\eta_{col}$ )	57 %
CS 350	2.52	Remark: Collector efficiency ( $\eta_{col}$ ) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m <sup>2</sup> , expressed in % and rounded to the nearest integer. Deviating from the regulation $\eta_{col}$ is based on reference area ( $A_{sol}$ ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2013.	
		Data required for CDR (EU) No 812/2013 - Reference Area $A_{sol}$	
		Zero-loss efficiency ( $\eta_0$ )	0.734 --
		First-order coefficient ( $a_1$ )	3.73 W/(m <sup>2</sup> K)
		Second-order coefficient ( $a_2$ )	0.0094 W/(m <sup>2</sup> K <sup>2</sup> )
		Incidence angle modifier IAM (50°)	0.95 --
		Remark: The data given in this section are related to collector reference area ( $A_{sol}$ ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.	