

Certificate number	16459 Rev.3	Replaces	16459 Rev.2
Issued	30/04/2020	First edition	12/12/2019
Report number	PKC0003438/B	Expiry date	11/12/2024
Page	1 of 1	Contract number	PKC0004007

Product Certificate Solar Thermal Products

License holder:	DualSun SAS 2 rue Marc Donadille, 13013 Marseille, France
Production site(s):	DualSun SAS ZA du Grand Champ 01640 Jujurieux, France
Product	Photovoltaic thermal collector
Model(s):	DualSun xxxM – 60 – 3BBPN (where “xxx” = rated power from 285W to 315W in steps of 5W)

Kiwa Cermet Italia hereby declares that the product can be considered complying to the testing requirements and is entitled to use the Solar Keymark Label, based upon the following aspects:

Laboratory testing of the solar thermal products, which are performed by an accredited laboratory in accordance to ISO/IEC 17025 -see annex-, using the following standards:

- ISO 9806:2017
Solar Energy – Solar Thermal Collectors – Test Methods

Specific CEN Keymark Scheme Rules for Solar Thermal Products SKN_N0444R3.

Periodic Inspection of the Factory site(s) performed by Kiwa Cermet Italia.

A description of the test results is given in the annex to this certificate.

Additional information according to the SKN_N0444_Annex P5.1 PVT_R1 of Solar Keymark Scheme Rules:

- PV module tested and certified according to the standards IEC 61215 and IEC 61730;
- Test reports nr.: L0003438/A rev.00; L0003438/C rev.00;
- Certificate of Conformity nr.: 16429 Rev.2;
- PV module: size 1650x991x35 mm; power range from 285W to 315W; backsheets colour black.

This certificate is issued in accordance with the Kiwa Cermet Italia regulations.

Publication of the certificate is allowed.

The validity of this certificate is subject to the positive result of periodic surveillance visits.

The validity of this certificate can be verified on request at the following e-mail address: energy@kiwacermet.it.

Any total or partial reproduction of this document in any form, without Kiwa Cermet Italia express authorization, is prohibited.

Kiwa Cermet Italia S.p.A.

Società con socio unico, soggetta all'attività di direzione e coordinamento di Kiwa Italia Holding Srl

Via Cadriano, 23
40057 Granarolo dell'Emilia (BO)

Tel +39.051.459.3.111

Fax +39.051.763.382


E-mail: info@kiwacermet.it
www.kiwa.it

Chief Operating Officer
Giampiero Belcredi




034



Annex to Solar Keymark Certificate					Licence Number		16459 Rev.3							
					Date issued		2020-04-30							
					Issued by		Kiwa Cermet Italia S.p.A.							
Licence holder		DualSun SAS			Country		France							
Brand (optional)					Web		http://www.dualsun.com							
Street, Number		2 Rue Marc Donadille			E-mail		contact@dualsun.fr							
Postcode, City		13013 Marseille			Tel		+33 413415371							
Collector Type					WISC (Wind and/or infrared sensitive collector)									
Collector name					Power output per collector									
					$G_b = 850 \text{ W/m}^2$, $G_d = 150 \text{ W/m}^2$ & $u = 1.3 \text{ m/s}$ $\vartheta_m - \vartheta_a$									
					0 K	10 K	30 K	50 K	70 K	80 K				
					m ²	mm	mm	mm	mm	mm	mm			
DualSun xxxM - 60 - 3BBPN (xxx = 285W to 315W in steps of 5W)					1,64	1.650	991	35	848	584	56	0	0	0
Power output per m ² gross area					519	357	34	0	0	0				
Performance parameters test method		Steady state - indoor												
Performance parameters (related to A _G)		η _{0, b}	a ₁	a ₂	a ₃	a ₄	a ₅	a ₆	a ₇	a ₈	K _d			
Units		-	W/(m ² K)	W/(m ² K ²)	J/(m ³ K)	-	J/(m ² K)	s/m	W/(m ² K ⁴)	W/(m ² K ⁴)	-			
Test results		0,503	16,91	0,000	0,452	0,50	17.198	0,043	0,04	0,000	0,99			
Incidence angle modifier test method		Steady state - indoor												
Incidence angle modifier		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°			
Transversal		K _{θT, coll}	0,97	0,98	1,01	1,09	1,10	1,07	0,80	0,40	0,00			
Longitudinal		K _{θL, coll}	0,97	0,98	1,01	1,09	1,10	1,07	0,80	0,40	0,00			
Heat transfer medium for testing					Water									
Flow rate for testing (per gross area, A _G)					dm/dt	0,033	kg/(sm ²)							
Maximum temperature difference during thermal performance test					($\vartheta_m - \vartheta_a$) _{max}	50	K							
Standard stagnation temperature (G = 1000 W/m ² ; $\vartheta_a = 30 \text{ }^\circ\text{C}$)					ϑ_{stg}	80	°C							
Maximum operating temperature					$\vartheta_{max, op}$	80	°C							
Maximum operating pressure					p _{max, op}	150	kPa							
Testing laboratory		CTCV			http://www.ctcv.pt									
Test report(s)		R05.1/2019 R07.1/2019			Dated		30/04/2020 30/04/2020							
Comments of testing laboratory					Datasheet version: 6.1, 2019-09-26									
Thermal performance parameters are given for the PV-module working with max. electrical power output ('MPP mode')					 CENTRO TECNOLÓGICO DE CERRANCA E DO VIEIRO Rua General Vinga Simão, 3026, 307 CERRANCA									
Kiwa Cermet Italia S.p.A. • Via Cadriano, 23 • 40057 Granarolo dell'Emilia (BO) • Italy Tel: +39 0514593111 • Fax: +39 051763382 • E-Mail: info@kiwacermet.it • www.kiwa.it														

Annex to Solar Keymark Certificate Supplementary Information	Licence Number	16459 Rev.3
	Issued	2020-04-30

Annual collector output in kWh/collector at mean fluid temperature ϑ_m													
Collector name	Standard Locations ϑ_m	Athens			Davos			Stockholm			Würzburg		
		25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
DualSun xxxM - 60 - 3BBPN (xxx = 285W to 315W in steps of 5W)		1.023	49	0	324	1		339	4		409	10	
Annual output per m ² gross area		626	30	0	198	1		208	3		250	6	
Annual efficiency, η_a		35%	2%	0%	12%	0%		18%	0%		20%	0%	
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18,5°C			3,2°C			7,5°C			9,0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (September 2019). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/													

Additional Information			
Collector heat transfer medium	Water		
The collector is deemed to be suitable for roof integration	No		
The collector was tested successfully under the following conditions:			
Climate class (A+, A, B or C)	A		--
G (W/m ²) >	1000	ϑ_a (°C) >	20
		H_x (MJ/m ²) >	600
Maximum tested positive load	2500		Pa
Maximum tested negative load	2500		Pa
Hail resistance using steel ball (maximum drop height)	0,8		m

Additional collector attribute(s)			
<input type="checkbox"/> Using external power source(s) for normal operation	<input type="checkbox"/> Active or passive measure(s) for self-protection		
<input checked="" type="checkbox"/> Co-generating thermal and electrical power	<input type="checkbox"/> Façade collector(s)		

Energy Labelling Information		Additional Informative Technical Data	
	Reference Area, A_{sol} (m ²)	Hydraulic Designation Code	Aperture Area, A_a (m ²)
DualSun xxxM - 60 - 3BBPN (xxx = 285W to 315W in steps of 5W)	1,64	163-VH-24R-A:4.5,1456-C:220,890	1,58

Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}		Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}		
Collector efficiency (η_{col})	-13%	Zero-loss efficiency (η_0)	0,52	
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		First-order coefficient (a_1)	16,14	
		Second-order coefficient (a_2)	0,000	
		Incidence angle modifier IAM (50°)	1,16	--
		Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.		