Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S1974 F
	Date of issue	30.08.2012

Company	emkaSol GmbH	**Country**		Deutschland
Brand (optional)		**Website**		www.emkasol.de
Street, number	Frankenstraße 35	**E-mail**		info@emkasol.de
Postal Code	71543	**Tel.**	+49	7945 941304
City	Wüstenrot	**Fax**	+49	7945 941329

Collector Type (flat plate / evacuate tubular / un-glazed)	Flat plate collector
Integration in the roof possible ?	No

Collector name	Aperture area (Aa) [m²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (AG) [m²]	Power output per collector unit G = 1000 W/m², Tm-Ta : 0 K [W]	10 K [W]	30 K [W]	50 K [W]	70 K [W]
Kollektortyp V4	1.81	2 020	1 020	95	2.06	1 352	1 280	1 123	950	762

Collector efficiency parameters related to aperture area (Aa) Type of fluid and flow rate see note 1	η_{0a}	0.747	-
	a_{1a}	3.889	W/(m²K)
	a_{2a}	0.011	W/(m²K²)
Stagnation temperature - Weather conditions see note 2	t_{stg}	193	°C
Effective thermal capacity	$c_{eff} = C/A_a$	11.6	kJ/(m²K)
Max. operation pressure - see note 3	p_{max}	1000	kPa

Incidence angle modifiers $K_\theta(\theta)$	G_{DIF}/G_{TOT} min	G_{DIF}/G_{TOT} max	θ_T / θ_L	50°	10°	20°	30°	40°	60°	70°
			$K_\theta(\theta_T)$	0.94	1.00	0.99	0.98	0.97	0.89	0.78
	-	-	$K_\theta(\theta_L)$	0.94	1.00	0.99	0.98	0.97	0.89	0.78

G_{DIF}/G_{TOT}: min&max - while measuring — ***Optional values***

Testing Laboratory	TZS, ITW University of Stuttgart
Website	www.tzs.uni-stuttgart.de
Test report id. number	09COL845
Date of test report	20.08.2012
Perf. test method	EN 12975-2 6.1.4 (outdoor)

Comments of testing laboratory :

none

Note 1	**Fluid**	Water	**Flow rate**	1.200	kg/s per m²
Note 2	**Irradiance, Gs=1000 W/m²** **Ambient temperature , Ta=30 °C**				
Note 3	**Given by manufacturer**				

TZS Forschungs- und Testzentrum für Solaranlagen
Institut für Thermodynamik und Wärmetechnik
Universität Stuttgart
Pfaffenwaldring 6, 70550 Stuttgart (Vaihingen)

VERSION 3.6, 2012.01.13

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S1974 F
	Issued	30.08.2012

Annual collector output kWh

	Location and collector temperature (Tm)														
	Athens			Davos			Stockholm			Würzburg					
Collector name	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C			
Kollektortyp V4	2 144	1 485	940	1 720	1 147	689	1 184	750	439	1 288	810	466			

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	**Collector orientation or tracking mode**
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). Detailed description with all equations used is available from the Solar Keymark web site (direct link: http://www.estif.org/solarkeymark/annexb1.php)

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin
Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de

Datasheet version:
VERSION 3.6, 2012.01.13
Calculation program version:
3.07, October 2011 (SP)