

Certificate number	16597 Rev.0	Replaces	-
Issued	23/06/2020	First edition	23/06/2020
Report number	PKC0004489	Expiry date	19/12/2023
Page	1 of 1	Contract number	PKC0004503

Product Certificate Solar Thermal Products

License holder:	ATAG Italia S.r.l. Via 11 Settembre, 6/1 – 37019 Peschiera del Garda (VR), Italy
Production site(s):	Via Venezia 11 – 37053 Cerea (VR), Italy
Product	Solar thermal collector
Model(s):	SOLDPF15T; SOLDPF18T

Kiwa Cermet Italia hereby declares that the product can be considered complying to the testing requirements and is entitled to use the Solar Keymark Label, based upon the following aspects:

Laboratory testing of the solar thermal products, which are performed by an accredited laboratory in accordance to ISO/IEC 17025 -see annex-, using the following standards:

- ISO 9806:2013
Solar Energy – Solar Thermal Collectors – Test Methods

Specific CEN Keymark Scheme Rules for Solar Thermal Products SKN_N0444R3.

Periodic Inspection of the Factory site(s) performed by Kiwa Cermet Italia.

A description of the test results is given in the annex to this certificate.

This certificate is issued in accordance with the Kiwa Cermet Italia regulations.

Publication of the certificate is allowed.

The validity of this certificate is subject to the positive result of periodic surveillance visits.

The validity of this certificate can be verified on request at the following e-mail address: energy@kiwacermet.it.

Any total or partial reproduction of this document in any form, without Kiwa Cermet Italia express authorization, is prohibited.

Kiwa Cermet Italia S.p.A.

Società con socio unico, soggetta all'attività di direzione e coordinamento di Kiwa Italia Holding Srl

Via Cadriano, 23

40057 Granarolo dell'Emilia (BO)

Tel +39.051.459.3.111

Fax +39.051.763.382

E-mail: info@kiwacermet.it

www.kiwa.it

Chief Operating Officer
Giampiero Belcredi




034



Annex to Solar Keymark Certificate	Licence Number	16597 Rev.0
Supplementary Information	Issued	2020-06-23

Annual collector output in kWh/collector at mean fluid temperature ϑ_m															
Collector name	Standard Locations			Athens			Davos			Stockholm			Würzburg		
	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C		
SOLDPF15T		3.459	3.096	2.647	2.980	2.583	2.148	2.155	1.835	1.492	2.314	1.975	1.607		
SOLDPF18T		4.155	3.719	3.180	3.580	3.103	2.581	2.589	2.204	1.793	2.779	2.372	1.930		
Annual output per m ² gross area		1.088	974	832	937	812	676	678	577	469	728	621	505		
Annual efficiency, η_a		62%	55%	47%	57%	50%	41%	58%	49%	40%	58%	50%	41%		
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)													
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²				
Mean annual ambient air temperature		18,5°C			3,2°C			7,5°C			9,0°C				
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°				
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (September 2019). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/															

Additional Information			
Collector heat transfer medium	Water-Glycole		
The collector is deemed to be suitable for roof integration	No		
The collector was tested successfully under the following conditions:			
Climate class (A+, A, B or C)			B
G (W/m ²) >	900	ϑ_a (°C) >	15
Maximum tested positive load			H _v (MJ/m ²) >
Maximum tested negative load			2416 Pa
Hail resistance using steel ball (maximum drop height)			2014 Pa
			m

Additional collector attribute(s)			
<input type="checkbox"/>	Using external power source(s) for normal operation	<input type="checkbox"/>	Active or passive measure(s) for self-protection
<input type="checkbox"/>	Co-generating thermal and electrical power	<input type="checkbox"/>	Façade collector(s)

Energy Labelling Information		Additional Informative Technical Data	
	Reference Area, A _{ref} (m ²)	Hydraulic Designation Code	Aperture Area, A _a (m ²)
SOLDPF15T	3,18	{F}-{O}-{CL}-{A:Ø,L}-{C:Ø,L}-{D}	2,87
SOLDPF18T	3,82	{F}-{O}-{CL}-{A:Ø,L}-{C:Ø,L}-{D}	3,45

Data required for CDR (EU) No 811/2013 - Reference Area A _{sol}		Data required for CDR (EU) No 812/2013 - Reference Area A _{sol}	
Collector efficiency (η_{col})	57%	Zero-loss efficiency (η_0)	0,61
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		First-order coefficient (a_1)	0,85
		Second-order coefficient (a_2)	0,009
		Incidence angle modifier IAM (50°)	1,03
		Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.	