TÜVRheinland®
DIN CERTCO

Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S1978 F
	Date of issue	05-10-2012

Company	F.D.E. SOLAR SRL	**Country**	Italy
Brand (optional)	FDE	**Website**	www.fdesolar.com
Street, number	Viale del Lavoro, 39	**E-mail**	info@fdesolar.com
Postal Code	37044	**Tel.**	+39 044284807
City	Cologna Veneta	**Fax**	+39 0442411140

Collector Type (flat plate / evacuate tubular / un-glazed)	Flat plate collector
Integration in the roof possible ?	No

Collector name	Aperture area (Aa) [m²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (AG) [m²]	Power output per collector unit G = 1000 W/m² Tm-Ta : 0 K [W]	10 K [W]	30 K [W]	50 K [W]	70 K [W]
FDE2.1AV	**1,86**	**2.120**	**1.025**	**90**	**2,17**	**1.427**	**1.347**	**1.173**	**981**	**772**
FDE2.6AV	2,38	2.125	1.275	95	2,71	1.825	1.723	1.501	1.256	988

Collector efficiency parameters related to aperture area (Aa) Type of fluid and flow rate see note 1	η_{0a}	0,767	-
	a_{1a}	4,187	W/(m²K)
	a_{2a}	0,012	W/(m²K²)
Stagnation temperature - Weather conditions see note 2	t_{stg}	185	°C
Effective thermal capacity	c_{eff} = C/Aa	5,48	kJ/(m²K)
Max. operation pressure - see note 3	p_{max}	900	kPa

Incidence angle modifiers $K_\theta(\theta)$	G_{DIF}/G_{TOT} min	G_{DIF}/G_{TOT} max	θ_T / θ_L	50°	*10°*	*20°*	*30°*	*40°*	*60°*	*70°*
			$K_\theta(\theta_T)$	0,92	*1,00*	*0,99*	*0,98*	*0,95*	*0,85*	*0,71*
	0,1	0,75	$K_\theta(\theta_L)$	0,92	*1,00*	*0,99*	*0,98*	*0,95*	*0,85*	*0,71*
G_{DIF}/G_{TOT}: min&max - while measuring					***Optional values***					

Testing Laboratory	TÜV Energie und Umwelt GmbH
Website	www.eco-tuv.de
Test report id. number	21220130_EN_AV; 21220130_P_AV
Date of test report	all: 05 October 2012
Perf. test method	EN 12975-2 6.3 (outdoor)

Comments of testing laboratory :

Note 1	**Fluid**	Water	**Flow rate**	0,022	kg/s per m²
Note 2	**Irradiance, Gs=1000 W/m²** **Ambient temperature , Ta=30 °C**				
Note 3	**Given by manufacturer**				

TÜV Rheinland Energie und Umwelt GmbH
Am Grauen Stein
D - 51105 Köln

VERSION 3.5, 2012.01.13

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S1978 F
	Issued	05-10-2012

Annual collector output kWh

	Location and collector temperature (Tm)														
	Athens			Davos			Stockholm			Würzburg					
Collector name	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C			
FDE2.1AV	**2.216**	**1.498**	**917**	**1.757**	**1.142**	**662**	**1.211**	**750**	**425**	**1.318**	**806**	**449**			
FDE2.6AV	2.835	1.917	1.173	2.248	1.461	847	1.550	960	544	1.687	1.031	575			

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	**Collector orientation or tracking mode**
Athens	38	1.765	18,5	South, 25°
Davos	47	1.714	3,2	South, 30°
Stockholm	59	1.166	7,5	South, 45°
Würzburg	50	1.244	9,0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). Detailed description with all equations used is available from the Solar Keymark web site (direct link:http://www.estif.org/solarkeymark/annexb1.php)

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin
Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de

Datasheet version:
VERSION 3.5, 2012.01.13
Calculation program version:
3.07, October 2011 (SP)