

Annex to Solar Keymark Certificate Supplementary Information	Licence Number	011-7S3032 F
	Issued	2021-07-14

Annual collector output in kWh/collector at mean fluid temperature ϑ_m													
Collector name	Standard Locations ϑ_m	Athens			Davos			Stockholm			Würzburg		
		25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
SF500-15DG-M		20'494	16'652	12'995	16'804	13'374	10'274	12'107	9'254	6'864	13'071	9'990	7'322
Annual output per m ² gross area		1'284	1'043	814	1'053	838	644	759	580	430	819	626	459
Annual efficiency, η_a		73%	59%	46%	65%	51%	39%	65%	50%	37%	66%	50%	37%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (September 2019). A detailed description of the calculations is available at <http://www.estif.org/solarkeymarknew/>

Additional Information			
Collector heat transfer medium	Water-Glycole		
The collector is deemed to be suitable for roof integration	No		
The collector was tested successfully under the following conditions:			
Climate class (A+, A, B or C)	A		--
G (W/m ²) >	1000	ϑ_a (°C) >	20
		H_x (MJ/m ²) >	600
Maximum tested positive load	1100 / 3000		Pa
Maximum tested negative load	1100 / 2400		Pa
Hail resistance using ice balls (diameter)	45		mm

Additional collector attribute(s)			
<input type="checkbox"/> Using external power source(s) for normal operation	<input type="checkbox"/> Active or passive measure(s) for self-protection		
<input type="checkbox"/> Co-generating thermal and electrical power	<input type="checkbox"/> Façade collector(s)		

Energy Labelling Information		Additional Informative Technical Data	
	Reference Area, A_{sol} (m ²)	Hydraulic Designation Code	Aperture Area, A_a (m ²)
SF500-15DG-M	15.96	X-H-LRS-A:X-C38.2,2520	14.83

Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}		Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}	
Collector efficiency (η_{col})	70%	Zero-loss efficiency (η_0)	0.80
		First-order coefficient (a_1)	2.33
		Second-order coefficient (a_2)	0.008
		Incidence angle modifier IAM (50°)	0.93
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.	