

Annex to Solar Keymark Certificate Supplementary Information	Licence Number	011-7S1880 F
	Issued	2017-04-26

Annual collector output in kWh/collector at mean fluid temperature ϑ_m, based on EN ISO 9806:2013 test results													
Standard Locations		Athens			Davos			Stockholm			Würzburg		
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
LNC/SPY 2.25V		2 448	1 804	1 245	1 893	1 362	914	1 387	946	610	1 503	1 021	647
LNC/SPY 2.25V (i)		2 448	1 804	1 245	1 893	1 362	914	1 387	946	610	1 503	1 021	647
LNC/SPY 2.25H		2 448	1 804	1 245	1 893	1 362	914	1 387	946	610	1 503	1 021	647
LNC/SPY 2.25H (i)		2 448	1 804	1 245	1 893	1 362	914	1 387	946	610	1 503	1 021	647
Annual output per m ² gross area		1 088	802	553	841	605	406	616	420	271	668	454	288
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1714 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 5.01 (March 2016). A detailed description of the calculations is available at www.solarkeymark.org/scenocalc													

Additional Information		
Collector heat transfer medium	Water-Glycole	
Hybrid Thermal and Photo Voltaic collector	No	
The collector is deemed to be suitable for roof integration	No	
The collector was tested successfully according to EN ISO 9806:2013 under the following conditions:		
Climate class (A, B or C)	C	--
Maximum tested positive load	2000	Pa
Maximum tested negative load	1500	Pa
Hail resistance using steel ball (maximum drop height)	-	m

Energy Labelling Information				
	Reference Area, A _{sol} (m ²)	Data required for CDR (EU) No 811/2013 - Reference Area A _{sol}		
LNC/SPY 2.25V	2.25	Collector efficiency (η_{col})	55	%
LNC/SPY 2.25V (i)	2.25	Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2013.		
LNC/SPY 2.25H	2.25			
LNC/SPY 2.25H (i)	2.25			
		Data required for CDR (EU) No 812/2013 - Reference Area A _{sol}		
		Zero-loss efficiency (η_0)	0.685	--
		First-order coefficient (a ₁)	2.93	W/(m ² K)
		Second-order coefficient (a ₂)	0.009	W/(m ² K ²)
		Incidence angle modifier IAM (50°)	0.93	--
Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.				