



Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S2029 F
	Date of issue	05-10-2012

Company	F.D.E. SOLAR SRL	Country	Italy
Brand (optional)	FDE	Website	www.fdesolar.com
Street, number	Viale del Lavoro, 39	E-mail	info@fdesolar.com
Postal Code	37044	Tel.	+39 044284807
City	Cologna Veneta	Fax	+39 0442411140

Collector Type (flat plate / evacuate tubular / un-glazed)	Flat plate collector
--	----------------------

Integration in the roof possible ?	No
------------------------------------	----

Collector name	Aperture area (A _a) [m ²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (A _g) [m ²]	Power output per collector unit G = 1000 W/m ² T _m -T _a :				
						0 K	10 K	30 K	50 K	70 K
						[W]	[W]	[W]	[W]	[W]
FDE2.1MV	1,87	2.125	1.025	95	2,18	1.416	1.336	1.163	973	764
FDE2.6MV	2,38	2.125	1.275	95	2,71	1.802	1.700	1.481	1.238	973

Collector efficiency parameters related to <u>aperture area (A_a)</u> Type of fluid and flow rate see note 1	η _{0a}	0,757	-
	a _{1a}	4,134	W/(m ² K)
	a _{2a}	0,012	W/(m ² K ²)

Stagnation temperature - Weather conditions see note 2	t _{stg}	217	°C
--	------------------	-----	----

Effective thermal capacity	C _{eff} = C/A _a	5,19	kJ/(m ² K)
----------------------------	-------------------------------------	------	-----------------------

Max. operation pressure - see note 3	p _{max}	900	kPa
--------------------------------------	------------------	-----	-----

Incidence angle modifiers K _θ (θ)	G _{DIF} /G _{TOT}		θ _T /θ _L	50°	10°	20°	30°	40°	60°	70°
	min	max								
	G _{DIF} /G _{TOT} : min&max - while measuring				0,90	1,00	0,99	0,97	0,94	0,82
Optional values				0,90	1,00	0,99	0,97	0,94	0,82	0,65

Testing Laboratory	TÜV Energie und Umwelt GmbH
Website	www.eco-tuv.de
Test report id. number	21220130_EN_MV; 21220130_P_MV
Date of test report	all: 05 October 2012
Perf. test method	EN 12975-2 6.3 (outdoor)

Comments of testing laboratory :

Note 1	Fluid	Water	Flow rate	0,022 kg/s per m ²
Note 2	Irradiance, G _s =1000 W/m ² Ambient temperature, T _a =30 °C			
Note 3	Given by manufacturer			





Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S2029 F
	Issued	05-10-2012

Annual collector output kWh														
Collector name	Location and collector temperature (T _m)													
	Athens			Davos			Stockholm			Würzburg				
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C		
FDE2.1MV	2.160	1.452	883	1.708	1.106	639	1.178	728	412	1.281	779	433		
FDE2.6MV	2.749	1.848	1.124	2.174	1.408	814	1.499	926	524	1.631	992	551		

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)
--	---

Overview of locations				
Location	Latitude °	G _{tot} kWh/m ²	T _a °C	Collector orientation or tracking mode
Athens	38	1.765	18,5	South, 25°
Davos	47	1.714	3,2	South, 30°
Stockholm	59	1.166	7,5	South, 45°
Würzburg	50	1.244	9,0	South, 35°

G _{tot}	Annual total irradiation on collector plane	kWh/m ²
T _a	Mean annual ambient air temperature	°C
T _m	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (T_m). Detailed description with all equations used is available from the Solar Keymark web site (direct link:<http://www.estif.org/solarkeymark/annexb1.php>)

DIN CERTCO • Alboinstraße 56 • 12103 Berlin Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de	Datasheet version: VERSION 3.5, 2012.01.13 Calculation program version: 3.07, October 2011 (SP)
--	--