

Annex to Solar Keymark Certificate							Licence Number		011-7S1939 F					
Supplementary Information							Issued		2019-07-29					
Annual collector output in kWh/collector at mean fluid temperature ϑ_m														
Standard Locations		Athens			Davos			Stockholm			Würzburg			
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	
KWB FlexiSun FK8250N		2 825	2 048	1 333	2 192	1 530	955	1 597	1 063	645	1 728	1 140	678	
Annual output per m ² gross area		1 121	813	529	870	607	379	634	422	256	686	452	269	
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)												
Annual irradiation on collector plane		1765 kWh/m ²			1714 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²			
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C			
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°			
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.0 (October 2018). A detailed description of the calculations is available at www.solarkeymark.org/scenocalc														
Additional Information														
Collector heat transfer medium										Water-Glycole				
The collector is deemed to be suitable for roof integration										No				
The collector was tested successfully under the following conditions:														
Climate class (A+, A, B or C)										B		--		
G (W/m ²) >		900		ϑ_a (°C) >		15		H _x (MJ/m ²) >		540				
Maximum tested positive load										3000		Pa		
Maximum tested negative load										2000		Pa		
Hail resistance using steel ball (maximum drop height)										n.a.		m		
Additional collector attribute(s)														
<input type="checkbox"/> Using external power source(s) for normal operation				<input type="checkbox"/> Active or passive measure(s) for self-protection										
<input type="checkbox"/> Co-generating thermal and electrical power				<input type="checkbox"/> Wind and/or infrared sensitive collector(s) (WISC)										
<input type="checkbox"/> Façade collector(s)														
Energy Labelling Information														
Reference Area, A _{sol} (m ²)		Hydraulic Designation Code												
KWB FlexiSun FK8250N		2.52					6,6-H-12S-A:7.2,2030-C21.4,1221							
Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}						Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}								
Collector efficiency (η_{col})						60%		Zero-loss efficiency (η_0)		0.75		--		
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.						First-order coefficient (a ₁)		2.98		W/(m ² K)				
						Second-order coefficient (a ₂)		0.018		W/(m ² K ²)				
						Incidence angle modifier IAM (50°)		0.89		--				
						Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.								
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany														
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de														