


Annex to Solar Keymark Certificate - Summary of EN ISO 9806:2013 Test Results					Licence Number		011-7S2445 F							
					Date issued		2017-07-12							
					Issued by		DIN CERTCO							
Licence holder		Solahart Industries Pty Ltd.			Country		Australia							
Brand (optional)					Web		www.rheem.com.au							
Street, Number		55 Brodie Street			E-mail		Reena.Subramaniam@rheem.com.au							
Postcode, City		2116, Rydalmere			Tel		+61 296 849 100							
Collector Type					Flat plate collector, glazed									
Collector name					Power output per collector Gb = 850 W/m ² ; Gd = 150 W/m ² ; u = 3 m/s $\vartheta_m - \vartheta_a$									
					0 K	10 K	30 K	50 K	70 K	109 K				
					m ²	mm	mm	mm	W	W	W	W	W	W
CSA2007 Collector					2.08	1 996	1 043	82	1 376	1 307	1 151	975	776	327
Power output per m² gross area					662	628	554	469	373	157				
Performance parameters test method					Quasi dynamic									
Performance parameters (related to AG)					$\eta_{0,b}$	c1	c2	c3	c4	c6	Kd			
Units					-	W/(m ² K)	W/(m ² K ²)	J/(m ³ K)	-	s/m	-			
Test results					0.670	3.209	0.013	0.000	0.000	0.000	0.916			
Incidence angle modifier test method					Quasi dynamic - outdoor									
Bi-directional incidence angle modifiers					No									
Incidence angle modifier					Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
Transversal					$K_{\theta T, coll}$	1.00	0.98	0.96	0.91	0.84	0.71	0.45	0.00	0.00
Longitudinal					$K_{\theta L, coll}$	1.00	0.98	0.96	0.91	0.84	0.71	0.45	0.00	0.00
Heat transfer medium for testing					Water									
Flow rate for testing (per gross area, A_G)					dm/dt	0.020	kg/(sm ²)							
Maximum temperature difference for thermal performance calculations					$(\vartheta_m - \vartheta_a)_{max}$	109	K							
Standard stagnation temperature (G = 1000 W/m²; $\vartheta_a = 30^\circ\text{C}$)					ϑ_{stg}	184	°C							
Effective thermal capacity, incl. fluid (per gross area, A_G)					C/m ²	13.42	kJ/(Km ²)							
Maximum operating temperature					$\vartheta_{max, op}$	100	°C							
Maximum operating pressure					$p_{max, op}$	1400	kPa							
Testing laboratory					TZS, ITW University Stuttgart			www.itw.uni-stuttgart.de						
Test report(s)					14COL1224/1 14COL1224Q/1			Dated		12.07.2017 12.07.2017				
Comments of testing laboratory					Datashet version: 5.01, 2016-03-01									
This data sheet replaces the data sheet issued on 10.11.2014 Documented performance parameters are taken from 14COL1224/1 The company address was updated					 Forschungs- und Testzentrum für Solaranlagen Institut für Thermodynamik und Wärmetechnik Universität Stuttgart Pfaffenwaldring 8, 70560 Stuttgart (Vaihingen)									
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de														

Annex to Solar Keymark Certificate Supplementary Information	Licence Number	011-7S2445 F
	Issued	2017-07-12

Annual collector output in kWh/collector at mean fluid temperature ϑ_m , based on ISO 9806:2013 test results													
Standard Locations	ϑ_m	Athens			Davos			Stockholm			Würzburg		
		25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
CSA2007 Collector		2 103	1 459	912	1 578	1 055	627	1 161	738	429	1 269	798	452
Annual output per m ² gross area		1 011	701	439	759	507	301	558	355	206	610	384	217
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1714 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 5.01 (March 2016). A detailed description of the calculations is available at www.solarkeymark.org/scenocalc													

Additional Information		
Collector heat transfer medium	Water-Glycole	
Hybrid Thermal and Photo Voltaic collector	No	
The collector is deemed to be suitable for roof integration	No	
The collector was tested successfully according to EN ISO 9806:2013 under the following conditions:		
Climate class (A, B or C)	A	--
Maximum tested positive load	3000	Pa
Maximum tested negative load	3000	Pa
Hail resistance using steel ball (maximum drop height)	2	m

Energy Labelling Information			
	Reference Area, A_{sol} (m ²)	Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}	
CSA2007 Collector	2.08	Collector efficiency (η_{col})	51 %
		Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2013.	
		Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}	
		Zero-loss efficiency (η_0)	0.662 --
		First-order coefficient (a_1)	3.21 W/(m ² K)
		Second-order coefficient (a_2)	0.013 W/(m ² K ²)
		Incidence angle modifier IAM (50°)	0.84 --
		Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.	