


<b>Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate</b>						<b>Licence Number</b>		<b>011-7S2507 F</b>				
						<b>Issued</b>		<b>2015-04-13</b>				
<b>Company holding the</b>		<b>Eco Jura Sp. z.o.o.</b>				<b>Country</b>		<b>Poland</b>				
<b>Brand (optional)</b>		<b>EcoJura</b>				<b>Website</b>		<b>-</b>				
<b>Street, street number</b>		<b>ul. 1 Maja 4</b>				<b>E-mail</b>		<b>Andrzej Zuwalski biuro@ecojura.pl</b>				
<b>Postal Code / City, province</b>		<b>42-202</b>		<b>Częstochowa</b>		<b>Tel/Fax</b>		<b>48 513 024 712 / -</b>				
<b>Collector Type (flat plate glazed/un-glazed; evacuate tubular)</b>						<b>Flat plate collector - glazed</b>						
Thermal / photo voltaic hybrid collector? (PVT collector)						No						
Integration in the roof possible ? (manufacturers declaration)						Yes						
	<b>Collector name</b>	<b>Aperture area (Aa)</b> m <sup>2</sup>	<b>Gross length</b> mm	<b>Gross width</b> mm	<b>Gross height</b> mm	<b>Gross area (AG)</b> m <sup>2</sup>	<b>Power output per collector module</b>					
							G = 1000 W/m <sup>2</sup>					
							Tm-Ta					
							0 K	10 K	30 K	50 K	70 K	
							W	W	W	W	W	
	<b>EcoJura Light 2.0</b>	<b>1.87</b>	<b>2 008</b>	<b>1 006</b>	<b>84</b>	<b>2.02</b>	<b>1 550</b>	<b>1 482</b>	<b>1 329</b>	<b>1 152</b>	<b>951</b>	
<b>Performance test method</b>						<b>Glazed liquid heating collector - steady state - indoor</b>						
<b>Performance parameters related to aperture area</b>			$\eta_0$	a1	a2							
<b>Units</b>			-	W/(m <sup>2</sup> K)	W/(m <sup>2</sup> K <sup>2</sup> )							
<b>Test results - Flow rate and fluid see note 1</b>			<b>0.831</b>	<b>3.469</b>	<b>0.016</b>							
<b>Bi-directional incidence angle modifiers?</b>		<b>No</b> <i>K<math>\theta</math> values are obligatory for 50°.</i>										
<b>Incidence angle modifiers K<math>\theta</math>(<math>\theta</math>)</b>		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°	
		K $\theta$ ( $\theta$ )	<b>1.00</b>	<b>0.98</b>	<b>0.96</b>	<b>0.92</b>	<b>0.86</b>	<b>0.75</b>	<b>0.52</b>	-	0.00	
<b>Incidence angle modifier not bi-directional - leave fields blank</b>												
<b>Stagnation temperature - Weather conditions see note 2</b>							<b>Tstg</b>	<b>193.7</b>		<b>°C</b>		
<b>Effective thermal capacity</b>							<b>ceff = C/Ag</b>	<b>6.19</b>		<b>kJ/(m<sup>2</sup>K)</b>		
<b>Max. intended operation temperature - see note 3</b>							<b>Tmax,op</b>	<b>208</b>		<b>°C</b>		
<b>Max. operation pressure - see note 3</b>							<b>pmax,op</b>	<b>600</b>		<b>kPa</b>		
<b>Pressure drop table - for a collector family, the values shall be for the module with highest <math>\Delta P</math> per m<sup>2</sup> aperture area</b>												
<b>Flow rate</b>		kg/(s m <sup>2</sup> )										
<b>Pressure drop, <math>\Delta P</math></b>		Pa										
<b>Optional weather data</b>		<b>Location</b>			<b>Link</b>							
<b>Testing Laboratory</b>		<b>TÜV Energie und Umwelt GmbH</b>										
<b>Website</b>		<b>www.eco-tuv.de</b>										
<b>Test report id. number</b>						<b>21225886.001_EcoJura</b>			<b>Date of test report</b>			<b>2015.04.13</b>
During the test GDIF/GTOT was always between			<b>0.07</b>	and	<b>0.97</b>							
<b>Comments of testing laboratory:</b>												
<b>Note 1</b>		<b>Flow rate</b>	<b>0.106</b> kg/(s m <sup>2</sup> )	<b>Fluid</b>	<b>Water</b>							
<b>Note 2</b>		<b>Irradiance, G = 1000 W/m<sup>2</sup>; Ambient temperature, Ta=30 °C</b>										
<b>Note 3</b>		<b>Given by manufacturer</b>										
											 <p>TÜV Rheinland Energie und Umwelt GmbH Am Grünen Stein D - 51105 Köln</p>	
Datasheet version: 4.05, 2013-11-07												
<b>DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany</b> <b>Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de</b>												



Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	011-7S2507 F
	Issued	13.04.2015

Annual collector output kWh/module														
Collector name	Location and collector temperature (Tm)													
	Athens			Davos			Stockholm			Würzburg				
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C		
EcoJura Light 2.0	2 313	1 670	1 101	1 782	1 249	797	1 303	869	537	1 409	930	564		

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)
---------------------------------------	---

Overview of locations				
Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). A detailed description of the calculations is available at <http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx>.