

Annex to Solar Keymark Certificate		Licence Number		011-7S 1924F													
Supplementary Information		Issued		2022-03-10													
Gross Thermal Yield in kWh/collector at mean fluid temperature ϑ_m																	
	Standard Locations	Athens			Davos			Stockholm			Würzburg						
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C				
Buderus CKN 2.0-s		2 310	1 584	974	1 710	1 126	653	1 270	789	443	1 389	857	473				
Gross Thermal Yield per m ² gross area		1 105	758	466	818	539	313	608	377	212	664	410	226				
Annual efficiency, η_a		63%	43%	26%	50%	33%	19%	52%	32%	18%	53%	33%	18%				
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)															
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²						
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C						
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°						
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.2 (13.01.2022). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/																	
Additional Information																	
Collector heat transfer medium										Water-Glycole							
The collector is deemed to be suitable for roof integration										No							
The collector was tested successfully under the following conditions:																	
Climate class (A+, A, B or C)										A+		--					
G (W/m ²) >		1100		ϑ_a (°C) >		40		H _x (MJ/m ²) >		700							
Maximum tested positive load										4000		Pa					
Maximum tested negative load										3000		Pa					
Hail resistance using ice balls (diameter)										35		mm					
Additional collector attribute(s)																	
Using external power source(s) for normal operation					No		Active or passive measure(s) for self-protection					No					
Co-generating thermal and electrical power					No		Façade collector(s)					No					
Energy Labelling Information						Additional Informative Technical Data											
Reference Area, A _{sol} (m ²)						Hydraulic Designation Code				Aperture Area, A _a (m ²)							
Buderus CKN 2.0-s						2.09				8-VH-1234S-A:5.2,1866-C:16.6,1070				1.95			
Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}						Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}											
Collector efficiency (η_{col})						52%		Zero-loss efficiency (η_0)				0.68		--			
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.						First-order coefficient (a ₁)				3.64		W/(m ² K)		--			
						Second-order coefficient (a ₂)				0.012		W/(m ² K ²)		--		--	
						Incidence angle modifier IAM (50°)				0.94		--		--		--	
Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.																	
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany																	
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de																	