

Annex to Solar Keymark Certificate Supplementary Information	Licence Number	011-7S1016 F
	Issued	2024-03-22

Gross Thermal Yield in kWh/collector at mean fluid temperature ϑ_m													
Collector name	Standard Locations	Athens			Davos			Stockholm			Würzburg		
	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
EKSV21P		2'264	1'505	922	1'653	1'080	643	1'222	747	426	1'336	805	453
EKSV26P		2'929	1'946	1'193	2'139	1'396	832	1'581	966	551	1'729	1'042	586
EKSV26H		2'929	1'946	1'193	2'139	1'396	832	1'581	966	551	1'729	1'042	586
Gross Thermal Yield per m ² gross area		1'127	749	459	823	537	320	608	372	212	665	401	225
Annual efficiency, η_a		64%	42%	26%	50%	33%	20%	52%	32%	18%	53%	32%	18%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Draft Ver. 6.2 (22.09.2021). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/													

Additional Information			
Collector heat transfer medium	Water-Glycole		
The collector is deemed to be suitable for roof integration	Yes		
The collector was tested successfully under the following conditions:			
Climate class (A+, A, B or C)			A
G (W/m ²) >	1000	ϑ_a (°C) >	20
		H_x (MJ/m ²) >	600
Maximum tested positive load			2400 Pa
Maximum tested negative load			2400 Pa
Hail resistance using ice balls (diameter)			35 mm

Additional collector attribute(s)			
Using external power source(s) for normal operation	No	Active or passive measure(s) for self-protection	No
Co-generating thermal and electrical power	No	Façade collector(s)	No

Energy Labelling Information		Additional Informative Technical Data	
	Reference Area, A_{sol} (m ²)	Hydraulic Designation Code	Aperture Area, A_a (m ²)
EKSV21P	2.01	9-V-1234S-A:7.2,1840-C:20.4,990-D	1.80
EKSV26P	2.60	12-V-1234S-A:7.2,1840-C:20.4,1290-D	2.37
EKSV26H	2.60	19-V-1234S-A:7.2,1140-C:20.4,1990-D	2.36

Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}		Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}	
Collector efficiency (η_{col})	53%	Zero-loss efficiency (η_0)	0.71
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		First-order coefficient (a_1)	4.30 W/(m ² K)
		Second-order coefficient (a_2)	0.006 W/(m ² K ²)
		Incidence angle modifier IAM (50°)	0.96
		Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.	