





Annex to Solar Keymark Certificate Supplementary Information	Licence Number	OEM 10093.2.2
	Issued	2022-10-10

Annual collector output in kWh/collector at mean fluid temperature $\vartheta_m$													
Collector name	Standard Locations	Athens			Davos			Stockholm			Würzburg		
	$\vartheta_m$	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
SCF-20/4B A		2.393	1.723	1.068	1.845	1.248	714	1.355	878	492	1.470	947	522
SCF-25/4B A		2.991	2.154	1.335	2.306	1.560	893	1.694	1.097	615	1.837	1.184	652
Annual output per m <sup>2</sup> gross area		1.197	862	534	923	624	357	677	439	246	735	474	261
Annual efficiency, $\eta_a$		68%	49%	30%	57%	38%	22%	58%	38%	21%	59%	38%	21%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m <sup>2</sup>			1630 kWh/m <sup>2</sup>			1166 kWh/m <sup>2</sup>			1244 kWh/m <sup>2</sup>		
Mean annual ambient air temperature		18,5°C			3,2°C			7,5°C			9,0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature  $\vartheta_m$  (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (September 2019). A detailed description of the calculations is available at <http://www.estif.org/solarkeymarknew/>

Additional Information			
Collector heat transfer medium	Water-Glycole		
The collector is deemed to be suitable for roof integration	No		
The collector was tested successfully under the following conditions:			
Climate class (A+, A, B or C)	A		--
G (W/m <sup>2</sup> ) >	1000	$\vartheta_a$ (°C) >	20
		$H_x$ (MJ/m <sup>2</sup> ) >	600
Maximum tested positive load	3000		Pa
Maximum tested negative load	3000		Pa
Hail resistance using steel ball (maximum drop height)	2		m

Additional collector attribute(s)			
<input type="checkbox"/>	Using external power source(s) for normal operation	<input type="checkbox"/>	Active or passive measure(s) for self-protection
<input type="checkbox"/>	Co-generating thermal and electrical power	<input type="checkbox"/>	Façade collector(s)

Energy Labelling Information		Additional Informative Technical Data	
	Reference Area, $A_{sol}$ (m <sup>2</sup> )	Hydraulic Designation Code	Aperture Area, $A_a$ (m <sup>2</sup> )
SCF-20/4B A	2,00	12-VH-1234S-A:7.2,1525-C:20.6,1255-	1,91
SCF-25/4B A	2,50	12-VH-1234S-A:7.2,1920-C:20.6,1255-	2,39

Data required for CDR (EU) No 811/2013 - Reference Area $A_{sol}$		Data required for CDR (EU) No 812/2013 - Reference Area $A_{sol}$	
Collector efficiency ( $\eta_{col}$ )	60%	Zero-loss efficiency ( $\eta_0$ )	0,76
Remark: Collector efficiency ( $\eta_{col}$ ) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m <sup>2</sup> , expressed in % and rounded to the nearest integer. Deviating from the regulation $\eta_{col}$ is based on reference area ( $A_{sol}$ ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		First-order coefficient ( $a_1$ )	2,99
		Second-order coefficient ( $a_2$ )	0,027
		Incidence angle modifier IAM (50°)	0,91
			--
Remark: The data given in this section are related to collector reference area ( $A_{sol}$ ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.			