


Annex to Solar Keymark Certificate					Licence Number		011-7S3128 F							
					Date issued		2022-06-27							
					Issued by		DIN CERTCO							
Licence holder		THERMIC SPLLC			Country		Greece							
Brand (optional)					Web		www.thermicsol.com							
Street, Number		Loutsas & Mesologgiou			E-mail		info@thermicsol.com							
Postcode, City		Mandra, Attica 19600			Tel		+30 210 555523							
Collector Type					Flat plate collector									
Collector name					Power output per collector									
					Gb = 850 W/m ² , Gd = 150 W/m ² & u = 1.3 m/s $\vartheta_m - \vartheta_a$									
					0 K	10 K	30 K	50 K	70 K	112 K				
					m ²	mm	mm	mm	mm	mm	mm			
THERMIC ZEUS 2,50 FP					2.52	2 006	1 257	85	1 915	1 824	1 628	1 413	1 181	634
Power output per m² gross area					760	724	646	561	469	252				
Performance parameters test method		Quasi dynamic												
Performance parameters (related to A_G)		$\eta_{0, b}$	a1	a2	a3	a4	a5	a6	a7	a8	Kd			
Units		-	W/(m ² K)	W/(m ² K ²)	J/(m ³ K)	-	J/(m ² K)	s/m	W/(m ² K ⁴)	W/(m ² K ⁴)	-			
Test results		0.761	3.53	0.009	0.000	0.00	13 480	0.000	0.00	0.0	0.99			
Incidence angle modifier test method		Quasi dynamic - outdoor												
Incidence angle modifier		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°			
Transversal		K _{θT, coll}	1.00	1.00	1.00	0.99	0.96	0.89	0.68	0.34	0.00			
Longitudinal		K _{θL, coll}	1.00	1.00	1.00	0.99	0.96	0.89	0.68	0.34	0.00			
Heat transfer medium for testing					Water-Glycole									
Flow rate for testing (per gross area, A_G)					dm/dt	0.020	kg/(sm ²)							
Maximum temperature difference during thermal performance test					($\vartheta_m - \vartheta_a$) _{max}	82	K							
Standard stagnation temperature (G = 1000 W/m²; $\vartheta_a = 30$ °C)					ϑ_{stg}	230	°C							
Maximum operating temperature					$\vartheta_{max, op}$	-	°C							
Maximum operating pressure					p _{max, op}	1000	kPa							
Testing laboratory		Institut für Gebäudeenergetik, Thermotechnik und Energiespeicherung (IGTE)					http://www.igte.uni-stuttgart.de							
Test report(s)		21COL1630OEM01 21COL1630QOEM01					Dated		01.06.2022 01.06.2022					
Comments of testing laboratory							Ver. 6.2 (13.01.2022)							
none							 Forschungs- und Testzentrum für Solaranlagen Institut für Thermodynamik und Wärmetechnik Universität Stuttgart Pfaffenwaldring 8, 70560 Stuttgart (Vaihingen)							
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de														

Annex to Solar Keymark Certificate							Licence Number		011-7S3128 F							
Supplementary Information							Issued		2022-06-27							
Gross Thermal Yield in kWh/collector at mean fluid temperature ϑ_m																
Standard Locations		Athens			Davos			Stockholm			Würzburg					
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C			
THERMIC ZEUS 2,50 FP		3 155	2 300	1 568	2 419	1 720	1 141	1 770	1 191	756	1 935	1 296	812			
Gross Thermal Yield per m ² gross area		1 252	913	622	960	683	453	702	473	300	768	514	322			
Annual efficiency, η_a		71%	52%	35%	59%	42%	28%	60%	41%	26%	62%	41%	26%			
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)														
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²					
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C					
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°					
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.2 (13.01.2022). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/																
Additional Information																
Collector heat transfer medium										Water-Glycole						
The collector is deemed to be suitable for roof integration										No						
The collector was tested successfully under the following conditions:																
Climate class (A+, A, B or C)										A		--				
G (W/m ²) >		1000		ϑ_a (°C) >		20		H_x (MJ/m ²) >		600						
Maximum tested positive load										3000		Pa				
Maximum tested negative load										2400		Pa				
Hail resistance using steel ball (maximum drop height)										2		m				
Additional collector attribute(s)																
Using external power source(s) for normal operation										No		Active or passive measure(s) for self-protection		No		
Co-generating thermal and electrical power										No		Façade collector(s)		No		
Energy Labelling Information							Additional Informative Technical Data									
Reference Area, A_{sol} (m ²)							Hydraulic Designation Code				Aperture Area, A_a (m ²)					
THERMIC ZEUS 2,50 FP							2.52				1"-V-1234S-7.2,1888-20.6,1310-D			2.32		
Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}							Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}									
Collector efficiency (η_{col})							60%									
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.							Zero-loss efficiency (η_0)				0.76			--		
							First-order coefficient (a_1)				3.53			W/(m ² K)		
							Second-order coefficient (a_2)				0.009			W/(m ² K ²)		
							Incidence angle modifier IAM (50°)				0.98			--		
Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.																
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany																
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de																