

Annex to Solar Keymark Certificate						Licence Number		011-7S3150 F					
Supplementary Information						Issued		2023-03-10					
Gross Thermal Yield in kWh/collector at mean fluid temperature ϑ_m													
	Standard Locations	Athens			Davos			Stockholm			Würzburg		
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
SolarWIN Klassik		2 772	1 969	1 245	2 099	1 420	841	1 551	997	573	1 694	1 085	613
Gross Thermal Yield per m ² gross area		1 165	827	523	882	597	353	651	419	241	712	456	258
Annual efficiency, η_a		66%	47%	30%	54%	37%	22%	56%	36%	21%	57%	37%	21%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.2 (13.01.2022). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/													
Additional Information													
Collector heat transfer medium								Water-Glycole					
The collector is deemed to be suitable for roof integration								Yes					
The collector was tested successfully under the following conditions:													
Climate class (A+, A, B or C)								A		--			
G (W/m ²) >		1000		ϑ_a (°C) >		20		H _x (MJ/m ²) >		600			
Maximum tested positive load								2750		Pa			
Maximum tested negative load								2250		Pa			
Hail resistance using ice balls (diameter)								35		mm			
Additional collector attribute(s)													
Using external power source(s) for normal operation						No		Active or passive measure(s) for self-protection				No	
Co-generating thermal and electrical power						No		Façade collector(s)				No	
Energy Labelling Information						Additional Informative Technical Data							
						Reference Area, A _{sol} (m ²)		Hydraulic Designation Code		Aperture Area, A _a (m ²)			
SolarWIN Klassik						2.38		10-VH-1234S-A:7.3,1920-C:20.8,1200		2.22			
Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}						Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}							
Collector efficiency (η_{col})						56%		Zero-loss efficiency (η_0)		0.72		--	
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.						First-order coefficient (a ₁)		3.31		W/(m ² K)			
						Second-order coefficient (a ₂)		0.017		W/(m ² K ²)			
						Incidence angle modifier IAM (50°)		0.95		--			
						Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.							
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany													
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de													