



Annex to Solar Keymark Certificate							Licence Number		011-7S1944 F						
Supplementary Information							Issued		2022-07-18						
<b>Gross Thermal Yield in kWh/collector at mean fluid temperature <math>\vartheta_m</math></b>															
Standard Locations		Athens			Davos			Stockholm			Würzburg				
Collector name	$\vartheta_m$	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C		
FK 26 W B		2 917	2 051	1 334	2 199	1 507	951	1 614	1 043	632	1 764	1 131	673		
Gross Thermal Yield per m <sup>2</sup> gross area		1 126	792	515	849	582	367	623	403	244	681	437	260		
Annual efficiency, $\eta_a$		64%	45%	29%	52%	36%	23%	53%	35%	21%	55%	35%	21%		
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)													
Annual irradiation on collector plane		1765 kWh/m <sup>2</sup>			1630 kWh/m <sup>2</sup>			1166 kWh/m <sup>2</sup>			1244 kWh/m <sup>2</sup>				
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C				
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°				
The collector is operated at constant temperature $\vartheta_m$ (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.2 (13.01.2022). A detailed description of the calculations is available at <a href="http://www.estif.org/solarkeymarknew/">http://www.estif.org/solarkeymarknew/</a>															
<b>Additional Information</b>															
Collector heat transfer medium							Water-Glycole								
The collector is deemed to be suitable for roof integration							No								
The collector was tested successfully under the following conditions:															
Climate class (A+, A, B or C)							A			--					
G (W/m <sup>2</sup> ) >		1000		$\vartheta_a$ (°C) >		20		H <sub>x</sub> (MJ/m <sup>2</sup> ) >		600					
Maximum tested positive load							3000			Pa					
Maximum tested negative load							2400			Pa					
Hail resistance using steel ball (maximum drop height)							1			m					
<b>Additional collector attribute(s)</b>															
Using external power source(s) for normal operation							No		Active or passive measure(s) for self-protection				No		
Co-generating thermal and electrical power							No		Façade collector(s)				No		
<b>Energy Labelling Information</b>							<b>Additional Informative Technical Data</b>								
Reference Area, A <sub>sol</sub> (m <sup>2</sup> )							Hydraulic Designation Code			Aperture Area, A <sub>a</sub> (m <sup>2</sup> )					
FK 26 W B							2.59			1-H-1234S-7.2,21329-16.6,1198-D			2.31		
Data required for CDR (EU) No 811/2013 - Reference Area A <sub>sol</sub>							Data required for CDR (EU) No 812/2013 - Reference Area A <sub>sol</sub>								
Collector efficiency ( $\eta_{col}$ )							55%			Zero-loss efficiency ( $\eta_0$ )		0.70		--	
Remark: Collector efficiency ( $\eta_{col}$ ) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m <sup>2</sup> , expressed in % and rounded to the nearest integer. Deviating from the regulation $\eta_{col}$ is based on reference area (A <sub>sol</sub> ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.							First-order coefficient (a <sub>1</sub> )		3.57		W/(m <sup>2</sup> K)				
							Second-order coefficient (a <sub>2</sub> )		0.009		W/(m <sup>2</sup> K <sup>2</sup> )				
							Incidence angle modifier IAM (50°)		0.96		--				
							Remark: The data given in this section are related to collector reference area (A <sub>sol</sub> ) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.								
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany															
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: <a href="mailto:info@dincertco.de">info@dincertco.de</a> • <a href="http://www.dincertco.de">www.dincertco.de</a>															