


Annex to Solar Keymark Certificate					Licence Number		011-7S3273 R							
					Date issued		2024-11-28							
					Issued by		DIN CERTCO							
Licence holder		PLAYSYSTEM SRL			Country		ITALY							
Brand (optional)		PSS			Web		www.pss-italy.com [pss-italy.com]							
Street, Number		Via G. Puccini n.8			E-mail		info@pss-italy.com							
Postcode, City		-80040- Poggiomarino (Napoli)			Tel		+39 081 338 16 06							
Collector Type					Evacuated tubular collector									
Collector name					Power output per collector									
					Gb = 850 W/m ² , Gd = 150 W/m ² & u = 1.3 m/s $\vartheta_m - \vartheta_a$									
					0 K	10 K	30 K	50 K	70 K	84 K				
					m ²	mm	mm	mm	mm	mm	mm			
					W	W	W	W	W	W				
PSS/P6-58/1800-10HP					2.24	1980	1130	133	1,298	1,262	1,152	994	788	619
PSS/P6-58/1800-12HP					2.67	1980	1350	133	1,551	1,507	1,377	1,188	942	740
PSS/P6-58/1800-15HP					3.33	1980	1680	133	1,930	1,876	1,713	1,479	1,172	920
PSS/P6-58/1800-18HP					3.98	1980	2010	133	2,309	2,244	2,050	1,769	1,402	1,101
PSS/P6-58/1800-20HP					4.42	1980	2230	133	2,562	2,490	2,274	1,963	1,556	1,222
PSS/P6-58/1800-22HP					4.85	1980	2450	133	2,815	2,736	2,498	2,156	1,709	1,342
PSS/P6-58/1800-24HP					5.29	1980	2670	133	3,068	2,981	2,723	2,350	1,863	1,463
PSS/P6-58/1800-25HP					5.50	1,980	2,780	133	3,194	3,104	2,835	2,447	1,940	1,523
PSS/P6-58/1800-28HP					6.04	1,980	3,050	133	3,504	3,406	3,110	2,684	2,128	1,671
Power output per m² gross area					580	564	515	444	352	277				
Performance parameters test method		Steady state - outdoor												
Performance parameters (related to A_G)		η_0, b	a1	a2	a3	a4	a5	a6	a7	a8	Kd			
Units		-	W/(m ² K)	W/(m ² K ²)	J/(m ³ K)	-	J/(m ² K)	s/m	W/(m ² K ⁴)	W/(m ² K ⁴)	-			
Test results		0.583	1.37	0.027	0.000	0.00	12220	0.000	0.00	0	0.97			
Incidence angle modifier test method		Steady state - outdoor												
Incidence angle modifier		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°			
Transversal		K _{GT, coll}	1.02	1.03	1.04	1.05	1.12	1.18	0.79	0.39	0.00			
Longitudinal		K _{GL, coll}	1.00	1.00	0.99	0.98	0.95	0.88	0.75	0.50	0.00			
Heat transfer medium for testing					Water									
Flow rate for testing (per gross area, A_G)					dm/dt	0.020	kg/(sm ²)							
Maximum temperature difference during thermal performance test					($\vartheta_m - \vartheta_a$) _{max}	53.72	K							
Standard stagnation temperature (G = 1000 W/m²; $\vartheta_a = 30$ °C)					ϑ_{stg}	280	°C							
Maximum operating temperature					$\vartheta_{max, op}$	230	°C							
Maximum operating pressure					p _{max, op}	1000	kPa							
Testing laboratory		Intertek Testing Services Shenzhen Ltd. Guangzhou Branch					http://www.intertek.com							
Test report(s)		231031204GZU-001 241031023GZU-001					Dated		2024/7/10 2024/11/28					
Comments of testing laboratory					Draft Ver. 6.2 (22.09.2021)									
All datas in this datasheet are come from Intertek Test Report 231031204GZU-001.					 Stamp & signature									
DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin, Germany Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de														

Annex to Solar Keymark Certificate Supplementary Information		Licence Number		011-7S3273 R									
		Issued		2024-11-28									
Gross Thermal Yield in kWh/collector at mean fluid temperature ϑ_m													
Collector name	Standard Locations	Athens			Davos			Stockholm			Würzburg		
	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
PSS/P6-58/1800-10HP		2,242	1,779	1,206	1,823	1,333	823	1,331	950	577	1,440	1,032	618
PSS/P6-58/1800-12HP		2,678	2,126	1,441	2,177	1,593	983	1,590	1,135	689	1,720	1,233	738
PSS/P6-58/1800-15HP		3,333	2,645	1,793	2,710	1,982	1,223	1,978	1,412	858	2,141	1,535	919
PSS/P6-58/1800-18HP		3,987	3,165	2,146	3,242	2,371	1,463	2,367	1,689	1,026	2,561	1,837	1,100
PSS/P6-58/1800-20HP		4,424	3,511	2,380	3,597	2,631	1,623	2,626	1,874	1,139	2,842	2,038	1,220
PSS/P6-58/1800-22HP		4,860	3,858	2,615	3,952	2,890	1,784	2,885	2,059	1,251	3,122	2,239	1,340
PSS/P6-58/1800-24HP		5,296	4,204	2,850	4,307	3,150	1,944	3,144	2,244	1,363	3,402	2,440	1,461
PSS/P6-58/1800-25HP		5,515	4,378	2,968	4,484	3,280	2,024	3,273	2,336	1,419	3,542	2,540	1,521
PSS/P6-58/1800-28HP		6,050	4,803	3,256	4,920	3,598	2,220	3,591	2,563	1,557	3,886	2,787	1,668
Gross Thermal Yield per m ² gross area		1,002	795	539	815	596	368	595	424	258	644	461	276
Annual efficiency, η_a		57%	45%	31%	50%	37%	23%	51%	36%	22%	52%	37%	22%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Draft Ver. 6.2 (22.09.2021). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/													
Additional Information													
Collector heat transfer medium										Water-Glycole			
The collector is deemed to be suitable for roof integration										No			
The collector was tested successfully under the following conditions:													
Climate class (A+, A, B or C)										B		--	
G (W/m ²) >		900		ϑ_a (°C) >		15		H_x (MJ/m ²) >		540			
Maximum tested positive load										2800		Pa	
Maximum tested negative load										1000		Pa	
Hail resistance using steel ball (maximum drop height)										0.6		m	
Additional collector attribute(s)													
Using external power source(s) for normal operation				No		Active or passive measure(s) for self-protection				No			
Co-generating thermal and electrical power				No		Façade collector(s)				No			
Energy Labelling Information						Additional Informative Technical Data							
		Reference Area, A_{sol} (m ²)		Hydraulic Designation Code			Aperture Area, A_a (m ²)						
PSS/P6-58/1800-10HP		2.24		1-H-12S-C:19,1205-D			1.82						
PSS/P6-58/1800-12HP		2.67		1-H-12S-C:19,1425-D			2.16						
PSS/P6-58/1800-15HP		3.33		1-H-12S-C:19,1755-D			2.70						
PSS/P6-58/1800-18HP		3.98		1-H-12S-C:19,2085-D			3.23						
PSS/P6-58/1800-20HP		4.42		1-H-12S-C:19,2305-D			3.59						
PSS/P6-58/1800-22HP		4.85		1-H-12S-C:19,2525-D			3.95						
PSS/P6-58/1800-24HP		5.29		1-H-12S-C:19,2745-D			4.41						
PSS/P6-58/1800-25HP		5.50		1-H-12S-C:19,2855-D			4.59						
PSS/P6-58/1800-28HP		6.04		1-H-12S-C:19,3185-D			5.24						
Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}						Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}							
Collector efficiency (η_{col})		48%				Zero-loss efficiency (η_0)		0.58		--			
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		First-order coefficient (a_1)		1.37		W/(m ² K)							
		Second-order coefficient (a_2)		0.027		W/(m ² K ²)							
		Incidence angle modifier IAM (50°)		1.02		--							
						Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.							
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany													
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de													